

Main

Product range	9050A/H
Product type	Timer
Timing mode	On-delay and off-delay
Timing range	0.1 s...1 min
Switch function	SPDT
Coil voltage	120 V AC 60 Hz 110 V AC 50 Hz
Contact operation	Time delayed 1 NO + 1 NC per head
Current rating	15 A

Complementary

Maximum switching voltage	600 V AC
Electrical connection	Screw-clamp terminals
Reset response time	29 Ms - on-delay 27 ms - off-delay
Mounting support	Panel

Environment

Ambient temperature range - operational	68...104 °F (20...40 °C)
Certifications	UL Listed CSA
Maximum Height	2.64 in (67 mm)
Maximum Width	5.67 in (144 mm)
Maximum Depth	4.37 in (111 mm)

Ordering and shipping details

Category	21631 - 9050 A ONE MINUTE PNEUMATIC TIMER
Discount Schedule	CP1
GTIN	00785901868026
Nbr. of units in pkg.	1
Package weight(Lbs)	2.4 lb(US) (1.09 kg)
Returnability	No
Country of origin	MX

Packing Units

Package 1 Height	25.40 in (64.516 cm)
Package 1 width	10.00 in (25.400 cm)
Package 1 Length	64.52 in (163.871 cm)

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds which is known to the State of California to cause Carcinogen & Reproductive harm. For more information go to www.p65warnings.ca.gov
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration

Contractual warranty

Warranty	18 months
----------	-----------