



Main

Product or component type	Starter
Type	S
Control Circuit Type	Common control circuit

Complementary

Control Circuit Voltage	208 V AC 60 Hz
Motor starter type	Non reversing
Current Rating	90 A
Number of Poles	3P
Number of Phases	3 phase
Horsepower Rating	25 HP 200 V AC 30 HP 230 V AC 50 HP 460 V AC 50 HP 575 V AC
Maximum Voltage Rating	600 V AC
Control Units	No control units
Thermal overload type	Melting alloy 3
Electrical connection	Screw clamp terminals
NEMA size	3
Maximum Height	33.50 in (851 mm)
Maximum Depth	11.93 in (303 mm)
Maximum Width	25.83 in (656 mm)

Environment

Enclosure Type	NEMA 4X glass polyester
Product certifications	CSA UL Listed NEMA

Ordering and shipping details

Category	21202 - 8502,36 S*R,S*T,S*W
Discount Schedule	CP1
GTIN	00785901517443
Nbr. of units in pkg.	1
Package weight(Lbs)	71.8 lb(US) (32.57 kg)
Returnability	No
Country of origin	MX

Offer Sustainability

EU RoHS Directive	Not compliant
China RoHS Regulation	 China RoHS Declaration

Contractual warranty

Warranty	18 months
----------	-----------