

XUC2ARCTL2

photo-electric sensor - XUC - thru beam - Sn
50m - 24..240VAC/DC - cable 2m



Main

Range of product	OsiSense XU
Series name	General purpose single mode
Electronic sensor type	Photo-electric sensor
Sensor name	XUC
Sensor design	Compact
Detection system	Thru beam
Material	Plastic
Type of output signal	Discrete
Supply circuit type	AC/DC
Wiring technique	5-wire
Discrete output function	1 C/O
Electrical connection	Cable
Cable length	6.56 ft (2 m)
Product specific application	-
Emission	Infrared thru beam
[Sn] nominal sensing distance	164.04 ft (50 m) thru beam

Complementary

Enclosure material	PC
Lens material	PMMA
Maximum sensing distance	196.85 ft (60 m)
Output type	Relay
Output function governance	Light or dark programmable
Add on output	Without
Cable composition	5 x 0.34 mm ²
Wire insulation material	PvR
Cable outer diameter	0.24 in (6 mm)
Status LED	1 LED yellow)output state 1 LED red)stability
[Us] rated supply voltage	24...240 V AC/DC
Supply voltage limits	20...264 V AC
Output voltage	<= 250 V AC
Switching capacity in mA	3 A cos φ = 1 for 0.5 million cycles at 1 operating cycle per second at 250 V)
Switching frequency	<= 20 Hz
Maximum power consumption in W	2 W
Time delay range	0...15 s monostable, on-delay or off-delay (programmable)
Maximum delay first up	60 ms
Maximum delay response	25 ms
Maximum delay recovery	25 ms
Setting-up	Sensitivity adjustment with potentiometer
Electrical durability	500000 cycles 3000 mA 1 60 cyc/mn 250 V
Maximum Depth	1.73 in (44 mm)
Maximum Height	4.41 in (112 mm)
Maximum Width	1.77 in (45 mm)
Net Weight	0.88 lb(US) (0.4 kg)
Kit composition	Transmitter + receiver

Environment

Product certifications	CSA CE UL
Ambient air temperature for operation	-13...131 °F (-25...55 °C)
Ambient air temperature for storage	-40...158 °F (-40...70 °C)
Vibration resistance	7 gn 10...55 Hz) IEC 60068-2-6
Shock resistance	20 gn 11 ms) IEC 60068-2-27
IP degree of protection	IP67 IEC 60529
NEMA degree of protection	NEMA 12IEC 60529 NEMA 13IEC 60529 NEMA 3IEC 60529 NEMA 4IEC 60529 NEMA 4XIEC 60529 NEMA 6IEC 60529 NEMA 6PIEC 60529



Ordering and shipping details

Category	22481 - SENSORS, PHOTOELECTRIC
Discount Schedule	DS2
GTIN	00785901328353
Nbr. of units in pkg.	1
Package weight(Lbs)	1.21 lb(US) (0.55 kg)
Returnability	No
Country of origin	FR

Packing Units

Package 1 Height	1.250 dm
Package 1 width	3.150 dm
Package 1 Length	0.900 dm

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Di-isodecyl phthalate (DIDP) and Diisononyl phthalate (DINP) which is known to the State of California to cause Carcinogen and Reproductive harm. For more information go to www.p65warnings.ca.gov
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)  EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	 Yes

Contractual warranty

Warranty	18 months
----------	-----------