Product data sheet Characteristics

9001SK1L7G

green illum pushbutton Ø 30 - flush spring return full guard - 220/240 V AC





Main				
Range of product	Harmony 9001SK			
Product or component type	Push-button			
Device short name	9001SK			
Rezel material	Plastic			

Complementary

Mounting diameter	1.18 in (30 mm)
Shape of signaling unit head	Octagonal
Type of operator	Spring return
Operator profile	Green flush, unmarked
Operator additional information	Full guard in plastic
Light source	incandescent
Bulb base	BA 9s
Light block supply	Direct 220240 V AC 50/60 Hz
Standards	CSA C22.2 No 14 UL 508 EN/IEC 60947-1 JIS C 852 EN/IEC 60947-5-4 EN/IEC 60947-5-1 JIS C 4520
Product certifications	CSA LR25490 class 3211 03 UL listed file E78403 CCN NKCR UL 508 NEMA
	INCINIA
Protective treatment	TC
Protective treatment Ambient air temperature for storage	
	TC
Ambient air temperature for storage	TC -40158 °F (-4070 °C)
Ambient air temperature for storage Ambient air temperature for operation	TC -40158 °F (-4070 °C) -13158 °F (-2570 °C)
Ambient air temperature for storage Ambient air temperature for operation Vibration resistance	TC -40158 °F (-4070 °C) -13158 °F (-2570 °C) 7 gn 2500 Hz)IEC 60068-2-6
Ambient air temperature for storage Ambient air temperature for operation Vibration resistance Shock resistance	TC -40158 °F (-4070 °C) -13158 °F (-2570 °C) 7 gn 2500 Hz)IEC 60068-2-6 50 gn IEC 60068-2-27
Ambient air temperature for storage Ambient air temperature for operation Vibration resistance Shock resistance Electrical shock protection class	TC -40158 °F (-4070 °C) -13158 °F (-2570 °C) 7 gn 2500 Hz)IEC 60068-2-6 50 gn IEC 60068-2-27 Class II IEC 61140
Ambient air temperature for storage Ambient air temperature for operation Vibration resistance Shock resistance Electrical shock protection class IP degree of protection	TC -40158 °F (-4070 °C) -13158 °F (-2570 °C) 7 gn 2500 Hz)IEC 60068-2-6 50 gn IEC 60068-2-27 Class II IEC 61140 IP66 IEC 60529 NEMA 1 NEMA 12 NEMA 13 NEMA 2 NEMA 3 NEMA 3 NEMA 3 NEMA 3R NEMA 4
Ambient air temperature for storage Ambient air temperature for operation Vibration resistance Shock resistance Electrical shock protection class IP degree of protection NEMA degree of protection	TC -40158 °F (-4070 °C) -13158 °F (-2570 °C) 7 gn 2500 Hz)IEC 60068-2-6 50 gn IEC 60068-2-27 Class II IEC 61140 IP66 IEC 60529 NEMA 1 NEMA 12 NEMA 13 NEMA 2 NEMA 3 NEMA 3 NEMA 3 NEMA 3R NEMA 4 NEMA 4X

Ordering and shipping details

Category	21429 - 9001 SK,SKY
Discount Schedule	CS1
GTIN	00785901838098
Nbr. of units in pkg.	1
Package weight(Lbs)	0.4 lb(US) (0.18 kg)
Returnability	No
Country of origin	MX

Offer Sustainability

Sustainable offer status	Green Premium product	
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds which is known to the State of California to cause Carcinogen & Reproductive harm. For more information go to www.p65warnings.ca.gov	
REACh free of SVHC	Yes	
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) [™] EU RoHS Declaration	
Toxic heavy metal free	Yes	
Mercury free	Yes	
RoHS exemption information	₫Yes	
China RoHS Regulation	☑ China RoHS Declaration	
Environmental Disclosure	Product Environmental Profile	
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.	

Contractual warranty

Contractual warranty		
Warranty	18 months	_