



Main

Product	Surge protection device
Device Short Name	EBA

Complementary

Surge Current	240 kA
Voltage Rating	208Y/120 V AC
Number of Phases	3 phase
Wiring Configuration	4-wire
Connection	Wire AWG 10 copper
MCOV	150 V
SCCR	200 kA
Local Signalling	Status LED green per phase normal operation Status LED red per phase fault
Provided Equipment	Alarm enable/disable switch Surge counter Dry contacts
Device Mounting	Surface
Height	13.32 in (338.3 mm)
Width	5.74 in (145.8 mm)
Depth	4.42 in (112.3 mm)
Cable length	24 in (609.60 mm)

Environment

Enclosure Rating	NEMA 1
Enclosure Material	Gray painted sheet steel
Standards	CSA C22.2 No 8 UL 1449:ed. 4 UL 96A:ed. 12 UL 1283
Ambient Operating	104 °F (40 °C)

Ordering and shipping details

Category	08464 - SURGE PROTECTION EMA
Discount Schedule	DE1B
GTIN	00785901627517
Nbr. of units in pkg.	1
Package weight(Lbs)	8 lb(US) (3.63 kg)
Returnability	No
Country of origin	MX

Packing Units

Package 1 Height	4.90 in (12.446 cm)
Package 1 width	5.90 in (14.986 cm)
Package 1 Length	13.80 in (35.052 cm)

Offer Sustainability

EU RoHS Directive	Compliant  EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	 Yes
China RoHS Regulation	 China RoHS Declaration