



## Main

Product	Surge protection device
Device Short Name	EBA

## Complementary

Surge Current	200 kA
Voltage Rating	208Y/120 V AC
Number of Phases	3 phase
Wiring Configuration	4-wire
Connection	Wire AWG 10 copper
MCOV	150 V
SCCR	200 kA
Local Signalling	Status LED green per phase normal operation Status LED red per phase fault
Provided Equipment	Alarm enable/disable switch Surge counter Dry contacts
Device Mounting	Surface
Height	13.32 in (338.3 mm)
Width	5.74 in (145.8 mm)
Depth	4.42 in (112.3 mm)
Cable length	24 in (609.60 mm)

## Environment

Enclosure Rating	NEMA 1
Enclosure Material	Gray painted sheet steel
Standards	CSA C22.2 No 8 UL 1449:ed. 4 UL 96A:ed. 12 UL 1283
Ambient Operating	104 °F (40 °C)

## Ordering and shipping details

Category	"08464 - SURGE PROTECTION EMA
Discount Schedule	DE1B
GTIN	00785901595786
Nbr. of units in pkg.	10
Package weight(Lbs)	10 lb(US) (4.54 kg)
Returnability	No
Country of origin	MX

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: DINP and DIDP which is known to the State of California to cause Carcinogen and Reproductive harm. For more information go to <a href="http://www.p65warnings.ca.gov">www.p65warnings.ca.gov</a>
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS Declaration</a>