

# Product data sheet

## Characteristics

# 8910DPA34V06

Contacteur, Definite Purpose, 30A, 4 pole, 20 HP at 575 VAC, 3 phase, 440/480 VAC 50/60 Hz coil, open



### Main

Product or component type	Definite Purpose Contactor
Line Rated Current	30 A
Number of Poles	4P
Pole contact composition	4 NO
Range of product	DPA

### Complementary

Maximum Horse Power Rating	2 Hp 115 V AC, 1 phase 5 Hp 230 V AC, 1 phase 10 Hp 230 V AC, 3 phase 15 Hp 460 V AC, 3 phase 20 hp 575 V AC, 3 phase
Locked rotor rated current	150 A 460 V AC 120 A 575 V AC 180 A 277 V AC
[Ue] rated operational voltage	600 V AC
[Uc] control circuit voltage	440 V AC 50 Hz 480 V AC 60 Hz
Phase	3 phase
Electrical connection	Quick connect terminals Binder head

### Environment

Product certifications	UL Recognized CSA
------------------------	----------------------




### Ordering and shipping details

Category	21343 - 8910 DPA 3_(30 AMP)
Discount Schedule	CP1B
GTIN	00785901024446
Nbr. of units in pkg.	1
Package weight(Lbs)	1.24 lb(US) (0.56 kg)
Returnability	No
Country of origin	CN

### Packing Units

Package 1 Height	3.30 in (8.382 cm)
Package 1 width	3.30 in (8.382 cm)
Package 1 Length	4.10 in (10.414 cm)

## Offer Sustainability

EU RoHS Directive	Compliant  <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	 <a href="#">Yes</a>
China RoHS Regulation	 <a href="#">China RoHS Declaration</a>

## Contractual warranty

Warranty	18 months
----------	-----------