



Main

Product	Energy Efficient Transformer
Enclosure Code	21D
Enclosure Type	NEMA 2
Insulation Temperature	428 °F (220 °C)
Phase	3 phase
Primary Voltage	480 V delta
Power Rating	112.5 kVA
Secondary Voltage	208Y/120 V
Full Capacity Taps	6 2.5 % 2+ 4-
Temperature Rise	150 °C
Winding Material	Copper

Ordering and shipping details

Category	16286 - 3 PH EE/TP1 >75 <=225 LVGP XFMR
Discount Schedule	PE2E
GTIN	00785901629535
Nbr. of units in pkg.	1
Package weight(Lbs)	792.15 lb(US) (359.31 kg)
Returnability	No
Country of origin	MX

Packing Units

Package 1 Height	3.50 ft (1.067 m)
Package 1 width	2.36 ft (0.719 m)
Package 1 Length	2.75 ft (0.838 m)

Offer Sustainability

Sustainable offer status	Green Premium product
REACH free of SVHC	Yes
EU RoHS Directive	Compliant  EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	 Yes
China RoHS Regulation	 China RoHS Declaration
Environmental Disclosure	 Product Environmental Profile

Contractual warranty

Warranty	18 months
----------	-----------