



### Main

Product or component type	Meter Socket
Meter socket type	Ringless
Hub type	Solid top

### Complementary

Meter socket rated current	200 A
Number of jaws	4 without jaw release
Bypass type	Horn bypass
Phase	1 phase
[Ue] rated operational voltage	600 V AC
Enclosure material	Steel
Electrical connection	Lugs 0.5" hex
Service feed location	UG
Wiring configuration	3-wire
AWG gauge	AWG 8...350 kcmil aluminium/copper)line side AWG 8...350 kcmil aluminium/copper)service ground

### Environment

Product certifications	UL Listed ANSI
Enclosure Rating	NEMA 3R

### Ordering and shipping details

Category	00039 - METER SOCKETS & HUBS
Discount Schedule	DE4
GTIN	00785901918196
Nbr. of units in pkg.	1
Package weight(Lbs)	1 lb(US) (0.45 kg)
Returnability	Yes
Country of origin	US

### Packing Units

Unit Type of Package 1	PCE
Package 1 Height	6.10 in (15.494 cm)
Package 1 width	13.70 in (34.798 cm)
Package 1 Length	18.50 in (46.99 cm)
Unit Type of Package 2	PAL
Number of Units in Package 2	42
Package 2 Weight	711.90 lb(US) (322.912 kg)

Package 2 Height	40.00 in (101.6 cm)
Package 2 width	36.00 in (91.44 cm)
Package 2 Length	48.00 in (121.92 cm)

Offer Sustainability

EU RoHS Directive	Under investigation
-------------------	---------------------

Contractual warranty

Warranty	18 months
----------	-----------