



Main

Product or component type	All-In-One
Range of product	Homeline
Meter socket type	Ringed
Hub type	B300 A

Complementary

Line Rated Current	200 A
Number of Phases	Single phase
Short-circuit current	10 kA
Mounting	Semi flush
Number of spaces	30
Number of circuits	40
Number of Tandem Breakers	10
Electrical connection	Lugs line side Lugs service ground
Wire Size	AWG 6...300 kcmil aluminium)line side AWG 6...300 kcmil copper)line side AWG 12...AWG 1/0 aluminium)service ground AWG 12...AWG 1/0 copper)service ground
Disconnect	Service disconnect (factory installed)
Disconnect Rating	200 A
Branch Breaker Rating	200 A
Service feed location	UG
Bypass type	No bypass
Connections - terminals	Lugs
Indoor/Outdoor Use	Surface mounting
Maximum Width	14.62 in (371.35 mm)
Maximum Depth	7.90 in (200.66 mm)
Maximum Height	48.00 in (1219.20 mm)

Environment

NEMA Rating	NEMA 3R
Product certifications	UL Listed

Ordering and shipping details

Category	00148 - HOMELINE CSED DEVICES
Discount Schedule	DE3A
GTIN	00785901291909
Nbr. of units in pkg.	1
Package weight(Lbs)	60 lb(US) (27.22 kg)
Returnability	Yes
Country of origin	MX

Packing Units

Package 1 Height	0.82 ft (0.249 m)
Package 1 width	1.43 ft (0.437 m)
Package 1 Length	4.08 ft (1.245 m)

Offer Sustainability

Sustainable offer status	Green Premium product
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile

Contractual warranty

Warranty	18 months
----------	-----------