SO2040M200SS ALL-IN-ONE RINGLESS OH200ASURFACEHORNSOL





Main	
Product or component type	All-In-One
Range of product	Homeline
Meter socket type	Ringed
Hub type	Δ

Complementary

Complementary	
Line Rated Current	200 A
Short-circuit current	22 kA
Mounting	Surface
Number of spaces	20
Number of circuits	40
Number of Tandem Breakers	20
Electrical connection	Lugs line side Lugs service ground
Wire Size	AWG 6350 kcmil aluminium/copper)line side AWG 8AWG 2/0 aluminium/copper)service ground
Tightening torque	Main lugs 250 lb.in, AWG 6350 kcmil, aluminium/copper Branch lugs 50 lb.in, AWG 14AWG 1/0, copper Branch lugs 50 lb.in, AWG 12AWG 1/0, aluminium Branch lugs 50 lb.in, AWG 3AWG 2/0, aluminium/copper Branch lugs 45 lb.in, AWG 6AWG 4, aluminium/copper Branch lugs 40 lb.in, AWG 8, aluminium/copper Branch lugs 35 lb.in, AWG 14AWG 10, aluminium/copper Branch lugs 35 lb.in, AWG 12AWG 10, aluminium/copper Cover 10 lb.in
Disconnect	Service disconnect (factory installed)
Disconnect Rating	200 A
Branch Breaker Rating	200 A
Service feed location	ОН
Bypass type	No bypass
Maximum Width	18.76 in (476.50 mm)
Maximum Depth	5.41 in (137.41 mm)
Maximum Height	41.18 in (1045.97 mm)

Ordering and shipping details

Category	00148 - HOMELINE CSED DEVICES
Discount Schedule	DE3A
GTIN	00785901967644
Nbr. of units in pkg.	1
Package weight(Lbs)	65 lb(US) (29.48 kg)
Returnability	No

Offer Sustainability

Sustainable offer status	Green Premium product	
REACh Regulation	☑ REACh Declaration	
REACh free of SVHC	Yes	
EU RoHS Directive	Compliant E EU RoHS Declaration	
Mercury free	Yes	
RoHS exemption information	₽¥Yes	
China RoHS Regulation	☑ China RoHS Declaration	
Environmental Disclosure	Product Environmental Profile	

Contractual warranty

Warranty	18 months
----------	-----------