



Main

Product	Miniature circuit-breaker
Range	QO
Voltage Rating	120/240 V AC 240 V AC 120 V AC
Mounting Type	Plug-in
Number of Poles	2P
Circuit Breaker Type	Standard
Ratings	HACR rated
Electrical Connection	Box lugs

Complementary

Interrupt Rating	10 KA 120/240 V AC 50/60 Hz 10 KA 240 V AC 50/60 Hz 10 kA 120 V AC 50/60 Hz
Wire Size	AWG 8...AWG 2 copper or aluminium
AWG gauge	44.25 lbf.in (5 N.m) 0.02...0.04 in ² (10...25 mm ²) AWG 8...AWG 2)

Environment

Certifications	UL Listed CSA
----------------	------------------

Ordering and shipping details

Category	00926-QO IND SPECIALTY CB
Discount Schedule	DE2A
GTIN	00785901088318
Package weight(Lbs)	12.00 oz (340.194 g)
Returnability	Yes
Country of origin	MX

Offer Sustainability

Sustainable offer status	Green Premium product
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
Halogen content performance	Halogen free product

Contractual warranty

Warranty	18 months
----------	-----------

Technical drawings of the 250 Series Push Button Switch, showing front, side, and top views with dimensions in inches and millimeters.

Front View Dimensions:

- Overall height: 3.5 in. (89 mm)
- Top section height: 2.25 in. (57 mm)
- Bottom section height: 3.00 in. (76 mm)
- Top section width: 2.23 in. (57 mm)
- Top section width (excluding mounting tabs): 2.09 in. (53 mm)
- Mounting tab width: 0.53 in. (13 mm)
- Bottom section width: 0.75 in. (19 mm) (two tabs)

Side View Dimensions:

- Overall height: 3.5 in. (89 mm)
- Top section height: 2.25 in. (57 mm)
- Bottom section height: 3.00 in. (76 mm)
- Top section width: 1.48 in. (38 mm)
- Top section width (excluding mounting tabs): 1.34 in. (34 mm)
- Mounting tab width: 0.53 in. (13 mm)
- Bottom section width: 0.75 in. (19 mm) (two tabs)

Top View Dimensions:

- Overall width: 2.75 in. (70 mm)
- Overall depth: 2.91 in. (74 mm)
- Mounting tab width: 0.75 in. (19 mm) (two tabs)
- Top section width: 0.59 in. (15 mm)
- Top section width (excluding mounting tabs): 0.38 in. (10 mm)
- Top section depth: 0.94 in. (24 mm)
- Top section depth (excluding mounting tabs): 0.16 in. (4 mm)
- Top section depth (excluding mounting tabs): 2.31 in. (59 mm)
- Top section depth (excluding mounting tabs): 2.5 in. (64 mm)
- Top section depth (excluding mounting tabs): 2.92 in. (74 mm)
- Top section depth (excluding mounting tabs): 0.25 in. (6 mm)

Switch Action Details:

- ON position: 22°
- OFF position: 21°
- Reset position: 26°
- Tripped position: 3°