



## Main

|                     |                                        |
|---------------------|----------------------------------------|
| Range               | Thalassa                               |
| Product name        | Thalassa TBP                           |
| Device application  | Multi-purpose                          |
| Category            | Industrial box                         |
| Maximum Height      | 4.57 in (116 mm)                       |
| Maximum Width       | 4.57 in (116 mm)                       |
| Maximum Depth       | 2.44 in (62 mm)                        |
| Internal height     | 4.13 in (105 mm)                       |
| Internal width      | 4.13 in (105 mm)                       |
| Internal depth      | 2.17 in (55 mm)                        |
| Enclosure mounting  | Wall mounted                           |
| Device composition  | 1 body<br>1 cover<br>4 cover screw     |
| Quantity per set    | Set of 5                               |
| Body type           | One piece moulded                      |
| Type of front cover | Low plain cover                        |
| Cover fixing        | Plastic screws                         |
| Lock type           | Captive screw flat outside sealed area |
| Removable parts     | Cover by captive screws                |

## Complementary

|                             |                        |
|-----------------------------|------------------------|
| Material                    | polycarbonate          |
| Color                       | Gray RAL 7035)         |
| Standards                   | IEC 62208<br>UL 508 A  |
| Product certifications      | TÜV<br>UL              |
| Electrical insulation class | Class II               |
| Mounting location           | Outdoor                |
| Net Weight                  | 0.38 lb(US) (0.171 kg) |

## Environment

|                                     |                            |
|-------------------------------------|----------------------------|
| IP degree of protection             | IP66 NEMA 4.4X             |
| IK degree of protection             | IK08 IEC 62262             |
| Fire resistance                     | 1760 °F (960 °C)           |
| Ambient air temperature for storage | 5...140 °F (-15...60 °C)   |
| Operating temperature               | -13...176 °F (-25...80 °C) |

## Ordering and shipping details

|                       |                                     |
|-----------------------|-------------------------------------|
| Category              | 80033 - ENCLOSURE SYSTEMS POLYESTER |
| Discount Schedule     | ES1                                 |
| GTIN                  | 00785901855088                      |
| Nbr. of units in pkg. | 5                                   |
| Package weight(Lbs)   | 1.72 lb(US) (0.78 kg)               |
| Returnability         | No                                  |
| Country of origin     | HU                                  |

## Packing Units

|                  |                       |
|------------------|-----------------------|
| Package 1 Height | 4.80 in (122.000 mm)  |
| Package 1 width  | 4.72 in (120.000 mm)  |
| Package 1 Length | 12.99 in (330.000 mm) |

## Offer Sustainability

|                            |                                                                                                |
|----------------------------|------------------------------------------------------------------------------------------------|
| Sustainable offer status   | Green Premium product                                                                          |
| REACH free of SVHC         | Yes                                                                                            |
| EU RoHS Directive          | Pro-active compliance (Product out of EU RoHS legal scope) <a href="#">EU RoHS Declaration</a> |
| Toxic heavy metal free     | Yes                                                                                            |
| Mercury free               | Yes                                                                                            |
| RoHS exemption information | <a href="#">Yes</a>                                                                            |
| China RoHS Regulation      | <a href="#">China RoHS Declaration</a>                                                         |
| Environmental Disclosure   | <a href="#">Product Environmental Profile</a>                                                  |

## Contractual warranty

|          |           |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|