

Main

Product range	9050A/H
Product type	Timer
Timing mode	Off-delay
Timing range	0.1 s...1 min
Switch function	DPDT
Coil voltage	120 V AC 60 Hz 110 V AC 50 Hz
Contact operation	Time delayed 2 NO + 2 NC
Current rating	10 A

Complementary

Maximum switching voltage	600 V AC
Electrical connection	Screw-clamp terminals
Reset response time	29 Ms - on-delay 27 ms - off-delay
Mounting support	Panel

Environment

Ambient temperature range - operational	68...104 °F (20...40 °C)
Certifications	CSA UL Listed
Maximum Height	2.64 in (67 mm)
Maximum Width	4.02 in (102 mm)
Maximum Depth	4.37 in (111 mm)

Ordering and shipping details

Category	21631 - 9050 A ONE MINUTE PNEUMATIC TIMER
Discount Schedule	CP1
GTIN	00785901866602
Nbr. of units in pkg.	1
Package weight(Lbs)	1.68 lb(US) (0.76 kg)
Returnability	No
Country of origin	MX

Packing Units

Package 1 Height	2.54 in (6.452 cm)
Package 1 width	1.00 in (2.540 cm)
Package 1 Length	6.45 in (16.387 cm)

Offer Sustainability

EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)  EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	 Yes
China RoHS Regulation	 China RoHS Declaration

Contractual warranty

Warranty	18 months
----------	-----------