389FXCXC1-120A

Power relay, Legacy, 3PDT, 20A, 120 VAC, side flange cover





Main

Product Type	Power relay
Switch Function	3PDT
Contact Composition	3 NO + 3 NC

Complementary

Input Current	20 A	
Contacts Material	Silver alloy contacts	
Minimum Switching Current	100 mA at 5 V DC	
Coil Resistance	1700 Ohm	
Input Voltage	120 V AC	
Drop-out Voltage Threshold	>= 0.1 Uc AC/DC	
Rated Operational Current	20 A at 150 V AC (on resistive load) conforming to UL 15 A at 250 V AC (on resistive load) conforming to UL 13 A at 28 V DC (on resistive load) conforming to UL 20 A at 150 V AC (ballast) conforming to UL 6.67 A at 277 V AC (ballast) conforming to UL 20 A at 250 V AC (NO/NC) conforming to IEC 15 A at 28 V DC (NO/NC) conforming to IEC	
Power consumption in W	1.3 W DC	
Power consumption in VA	2 VA AC	
Voltage Range	0.851.1 Uc AC	
Maximum Switching Voltage	300 V AC	
Motor Power HP	0.5 hp at 120/240 V AC 50/60 Hz	
Connections Terminals	Quick	
Mounting	Flange	
Product Weight	2.96 oz (84 g)	

Environment


Ambient Air Temperature for Operation	-22131 °F (-3055 °C)	
Ambient Air Temperature for Storage	-22185 °F (-3085 °C)	
Product Certifications	CURus CSA CE RoHS	
Electrical Durability	100000 Cycles resistive load 50000 cycles resistive DC load	
Mechanical Durability	5000000 cycles	
Dielectric Strength	2200 V AC between coil and contact 2200 V AC between poles 1600 V AC between contacts	

Ordering and shipping details

GTIN	03606480276910
Offer Sustainability	
Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Nickel compounds, which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	☑ REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	₽¥Yes
China RoHS Regulation	☐ China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
WEEE	The product must be disposed on European Union markets following specif waste collection and never end up in rubbish bins.

Connections and Wiring Diagrams





SPST-NO-(DM)

Connections and Wiring Diagrams

