Product data sheet Characteristics

XS7D1A1NAM12

inductive sensor XS7 80x80x26 - PBT - Sn40mm - 12..24VDC - M12





Main

Range of product	OsiSense XS	
Series name	General purpose	
Sensor type	Inductive proximity sensor	
Device application	-	
Sensor name	XS7	
Sensor design	Flat form 80 x 80 x 26	
Size	26 mm	
Body type	Fixed	
Detector flush mounting acceptance	Flush mountable	
Material	Plastic	
Enclosure material	PBT	
Type of output signal	Discrete	
Wiring technique	3-wire	
Discrete output function	1 NO	
Output circuit type	DC	
Discrete output type	NPN	
Electrical connection	4 pins M12 male connector	
[Us] rated supply voltage	1224 V DC reverse polarity protection	
Switching capacity in mA	<= 100 mA DC overload and short-circuit protection	
IP degree of protection	IP67 double insulation IEC 60529	

Complementary

Detection face	Frontal
Front material	PBT
Operating zone	0.001.26 in (032 mm)
Differential travel	115% of Sr
Status LED	Output state 1 LED yellow)
Supply voltage limits	1036 V DC
Switching frequency	<= 100 Hz
Maximum voltage drop	<2 V closed)
Current consumption	<= 10 mA no-load
Maximum delay first up	30 ms
Maximum delay response	5 ms
Maximum delay recovery	35 ms
Marking	CE
Depth	1.02 in (26 mm)
Height	3.15 in (80 mm)
Width	3.15 in (80 mm)

Environment

Product certifications	UL C-tick CSA Ecolab
Ambient air temperature for operation	-13158 °F (-2570 °C)
Ambient air temperature for storage	-40185 °F (-4085 °C)
Vibration resistance	25 gn +/- 2 mm 1055 Hz)IEC 60068-2-6
Shock resistance	50 gn 11 ms IEC 60068-2-27

Ordering and shipping details

Category	22486 - SENSORS, PROXIMITY
Discount Schedule	DS2
GTIN	00785901293439
Nbr. of units in pkg.	1
Package weight(Lbs)	1 lb(US) (0.45 kg)
Returnability	No
Country of origin	ID

Packing Units

Package 1 Height	0.420 dm
Package 1 width	0.950 dm
Package 1 Length	1.320 dm

Offer Sustainability

ustainable offer status Green Premium product		
California proposition 65	WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov	
REACh Regulation	REACh Declaration	
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EV EU RoHS Declaration	
Mercury free	Yes	
RoHS exemption information	₽¥Yes	
Environmental Disclosure	Product Environmental Profile	

Contractual warranty

Warranty 18 months		
Warranty 18 months		
	10 months	
•		