



## Main

Product	Single Throw Safety Switch
Current Rating	400 A
Certifications	UL listed file E2875
Enclosure Rating	NEMA 1
Disconnect Type	Non-fusible disconnect switch
Factory Installed Neutral	None
Mounting Type	Surface
Number of Poles	3
Electrical Connection	Lugs
Duty Rating	General duty
Voltage Rating	240 V AC
Wire Size	AWG 1/0...600 kcmil aluminium/copper 2 x AWG 1/0...2 x 300 kcmil aluminium/copper

## Complementary

Short-circuit withstand	200 kA
Maximum Horse Power Rating	125 hp 240 V AC 60 Hz 3 phase NEC 430.52
Maximum Width	24.88 in (631.95 mm)
Height	45.12 in (1146.05 mm)
Depth	8.88 in (225.55 mm)
Tightening torque	340 Lbf.in (38.41 N.m) AWG 1/0...750 kcmil 340 lbf.in (38.41 N.m) 2 x AWG 1/0...2 x 300 kcmil

## Ordering and shipping details

Category	00007 - D & DU SW, NEMA1, 400-600A
Discount Schedule	DE1A
GTIN	00785901491910
Nbr. of units in pkg.	1
Package weight(Lbs)	115 lb(US) (52.16 kg)
Returnability	Yes
Country of origin	MX

## Packing Units

Unit Type of Package 1	PCE
Package 1 Height	11.30 in (28.7 cm)
Package 1 width	25.98 in (66 cm)
Package 1 Length	50.00 in (127 cm)

## Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>
REACH Regulation	<a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
PVC free	Yes
Halogen content performance	Halogen free plastic parts product

## Contractual warranty

Warranty	18 months
----------	-----------