70S2-04-C-12-N

Relay, Legacy, solid state, SPST, 12A, 24... 280 VAC, 3...30/32 VDC Uc, triac, panel mount, blade terminal



Main

Range	Legacy
Product Type	Solid state relay
Nominal Output Current	12 A AC
Network Number of Phases	1 phase
Mounting Support	Panel mounted
Output Voltage	24280 V AC

Complementary

Complementary	
Holding Current	50 mA
Input Current Limits	716 mA 330 V DC typical
Switch Function	SPST
Contacts Type and Composition	NO
Protection Type	Reverse polarity 3 V DC control
Connections Terminals	Blade terminal
Switching Voltage	1 V DC tripping
Switching Device	Triac output Zero voltage switching
Maximum Peak Voltage	600 V
Surge Current	150 A 1 cycle 48 A 60 cycles
Must Release Voltage	1 V
Voltage Drop	<1.6 V on-state AC
Thermal Resistance	2.4 °C/W
Leakage Current	6 mA at off-state
DV/dt	300 V/ms off-state at maximum rated voltage
Response Time	8.33 ms turn-on, turn-off)
Dielectric Strength	3000 V between input and output 3000 V between terminals and chassis
Height	0.88 in (22.25 mm)
Width	1.03 in (26.2 mm)
Depth	1.23 in (31.2 mm)
Product Weight	1.66 oz (47 g)

Environment

Product Certifications	UL Recognized CSA CE RoHS
Ambient Air Temperature for Operation	-40212 °F (-40100 °C)
Ambient Air Temperature for Storage	-40257 °F (-40125 °C)

Ordering and shipping details

	GTIN 03606480278556	
--	---------------------	--

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov	
REACh Regulation	☑ REACh Declaration	
REACh free of SVHC	Yes	
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)	
Mercury free	Yes	
RoHS exemption information	₫Yes	
China RoHS Regulation	China RoHS Declaration	
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.	

Connections and Wiring Diagrams

