

Product data sheet

Characteristics

8910DPA32V09

Contactor, Definite Purpose, 30A, 2 pole, 5 HP at 230 VAC, 1 phase, 208/240 VAC 60 Hz 220 VAC 50 Hz coil, open



Main

| | |
|---------------------------|----------------------------|
| Product or component type | Definite Purpose Contactor |
| Line Rated Current | 30 A |
| Number of Poles | 2P |
| Pole contact composition | 2 NO |
| Range of product | DPA |

Complementary

| | |
|--------------------------------|----------------------------------------------------|
| Maximum Horse Power Rating | 2 Hp 115 V AC, 1 phase 5 hp 230 V AC, 1 phase |
| Locked rotor rated current | 150 A 460 V AC 120 A 575 V AC 180 A 277 V AC |
| [Ue] rated operational voltage | 600 V AC |
| [Uc] control circuit voltage | 208...240 V AC 60 Hz 220 V AC 50 Hz |
| Phase | 1 phase |
| Electrical connection | Quick connect terminals Binder head |

Environment

| | |
|------------------------|----------------------|
| Product certifications | UL Recognized CSA |
|------------------------|----------------------|

Ordering and shipping details

| | |
|-----------------------|-----------------------------|
| Category | 21343 - 8910 DPA 3_(30 AMP) |
| Discount Schedule | CP1B |
| GTIN | 00785901749813 |
| Nbr. of units in pkg. | 1 |
| Package weight(Lbs) | 0.98 lb(US) (0.44 kg) |
| Returnability | Yes |
| Country of origin | CN |

Packing Units

| | |
|------------------|---------------------|
| Package 1 Height | 2.60 in (6.604 cm) |
| Package 1 width | 3.20 in (8.128 cm) |
| Package 1 Length | 4.00 in (10.160 cm) |

Offer Sustainability

| | |
|----------------------------|-----------------------------------------------|
| REACH Regulation | REACH Declaration |
| EU RoHS Directive | Compliant EU RoHS Declaration |
| Mercury free | Yes |
| RoHS exemption information | Yes |
| China RoHS Regulation | China RoHS Declaration |

Contractual warranty

| | |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|

Approximate Dimensions

