

H364RBVW

Safety switch, heavy duty, fusible, 200A, 3 poles, 150 hp, 600 VAC/DC, NEMA 3R, bolt-on hub, viewing window



Main

Product	Single Throw Safety Switch
Current Rating	200 A
Number of Poles	3
Voltage Rating	600 V AC/DC
Wire Size	AWG 6...250 kcmil copper or aluminium
Disconnect Type	Fusible disconnect
Mounting Type	Surface
Factory Installed Neutral	None
Duty Rating	Heavy duty
Certifications	UL listed file E2875
Enclosure Rating	NEMA 3R galvanized steel

Complementary

Maximum Horse Power Rating	50 Hp 480 V AC 50...60 Hz 3 phase NEC 240.6 125 Hp 480 V AC 50...60 Hz 3 phase NEC 430.52 60 Hp 600 V AC 50...60 Hz 3 phase NEC 240.6 150 Hp 600 V AC 50...60 Hz 3 phase NEC 430.52 40 Hp 250 V DC 50 hp at 600 V DC
Maximum Width	18.63 in (473.20 mm)
Height	29.25 in (742.95 mm)
Depth	8.5 in (215.90 mm)
Tightening torque	275 lbf.in (31.07 N.m) 0.02...0.20 in ² (13.3...127 mm ²) AWG 6...250 kcmil

Ordering and shipping details

Category	00117 - H&HU SW,VIEW WINDOW(VW)
Discount Schedule	DE1
GTIN	00785901265436
Nbr. of units in pkg.	1
Package weight(Lbs)	44.6 lb(US) (20.23 kg)
Returnability	No
Country of origin	US

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
RECh Regulation	RECh Declaration
RECh free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes

China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
PVC free	Yes
Contractual warranty	
Warranty	18 months