Product data sheet Characteristics

XS7E1A1NBM8

inductive sensor XS7 26x26x13 - PBT - Sn10mm - 12..24VDC - M8





Main

Range of product	OsiSense XS	
Series name	General purpose	
Sensor type	Inductive proximity sensor	
Device application	-	
Sensor name	XS7	
Sensor design	Flat form 26 x 26 x 13	
Size	13 mm	
Body type	Fixed	
Detector flush mounting acceptance	Flush mountable	
Material	Plastic	
Enclosure material	PBT	
Type of output signal	Discrete	
Wiring technique	3-wire	
Discrete output function	1 NC	
Output circuit type	DC	
Discrete output type	NPN	
Electrical connection	3 pins M8 male connector	
[Us] rated supply voltage	1224 V DC reverse polarity protection	
Switching capacity in mA	<= 100 mA DC overload and short-circuit protection	
IP degree of protection	IP67 IEC 60529	

Complementary

Complementary	
Detection face	Frontal
Front material	PBT
Operating zone	0.000.31 in (08 mm)
Differential travel	115% of Sr
Status LED	Output state 1 LED yellow)
Supply voltage limits	1036 V DC
Switching frequency	<= 1000 Hz
Maximum voltage drop	<2 V closed)
Current consumption	<= 10 mA no-load
Maximum delay first up	10 ms
Maximum delay response	2 ms
Maximum delay recovery	6 ms
Marking	CE
Depth	0.51 in (13 mm)
Height	1.02 in (26 mm)
Maximum Width	1.02 in (26 mm)
Net Weight	0.09 lb(US) (0.04 kg)

Environment

Product certifications	C-tick UL CSA Ecolab
Ambient air temperature for operation	-13158 °F (-2570 °C)
Ambient air temperature for storage	-40185 °F (-4085 °C)
Vibration resistance	25 gn +/- 2 mm 1055 Hz)IEC 60068-2-6
Shock resistance	50 gn 11 ms IEC 60068-2-27

Ordering and shipping details

Category	22486 - SENSORS, PROXIMITY
Discount Schedule	DS2
GTIN	03389110140095
Nbr. of units in pkg.	1
Package weight(Lbs)	1 lb(US) (0.45 kg)
Returnability	No
Country of origin	ID

Packing Units

Unit Type of Package 1	PCE	
Package 1 Height	1.65 in (4.2 cm)	
Package 1 width	3.74 in (9.5 cm)	
Package 1 Length	2.60 in (6.6 cm)	

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	☑ REACh Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EEU RoHS Declaration
Mercury free	Yes
RoHS exemption information	₽¥Yes
Environmental Disclosure	Product Environmental Profile

Contractual warranty

Warranty	18 months