



Overview

Lead time	Usually in Stock
-----------	------------------

Physical

Cable length	6.5 ft (1.98 m)
Color	Beige
Depth	5.55 in (14.1 cm)
Height	4.57 in (11.6 cm)
Mounting preference	No preference
Net Weight	9.70 lb(US) (4.4 kg)
Mounting mode	Not rack-mountable
Maximum Width	8.43 in (21.4 cm)

Input

Input Frequency	50/60 Hz
Plug standard	NEMA 5-15P
Number of cables	1
Nominal Input Voltage	120 V

Output

Kw Rating	1200 W
Max Configurable Power (Watts)	1200 W
Output voltage	120 V
Rated power in VA	1200 VA

Conformance

Product certifications	CUL Listed NOM
Standards	FCC Part 15 class B UL 1012
Equipment protection policy	Lifetime : \$25000

Environmental

Ambient air temperature for operation	32...104 °F (0...40 °C)
Relative humidity	5...95 %
Operating altitude	0...10000 ft
Ambient air temperature for storage	-13...149 °F (-25...65 °C)
Storage altitude	0...50000 ft (0.00...15240.00 m)

Batteries & Runtime

Included Battery Modules	0
Battery Slots Empty	0
Liquid Electrolyte Value	0

Surge Protection and Filtering

Surge energy rating	680 J
---------------------	-------

Ordering and shipping details

GTIN	00731304197911
Package weight(Lbs)	10.36 lb(US) (4.7 kg)

Packing Units

Package 1 Height	6.89 in (17.5 cm)
Package 1 width	10.75 in (27.3 cm)
Package 1 Length	8.15 in (20.7 cm)
SCC14	10731304197918
Number of Units in Package 2	4
Package 2 Weight	43 lb(US) (19.50 kg)
Package 2 Length	16.73 in (424.94 mm)
Number of Units in Package 3	64

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov
EU RoHS Directive	Under investigation

Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------