

Product Environmental Profile

Rack PDU 2G, Metered by Outlet with Switching with Power Cord

Metered-by-outlet with switching Rack PDUs provide real-time remote monitoring of each individual outlet.






General information

Representative product	Rack PDU 2G, Metered by Outlet with Switching with Power Cord - AP8659
Description of the product	Individual outlet level power metering provides a more granular view of the power distributed to equipment within the enclosure. It also provides the ability to analyze component power trends and perform capacity planning.
Description of the range	Metered-by-outlet with switching Rack PDUs provide real-time remote monitoring of each individual outlet. The environmental impacts of this referenced product are representative of the impacts of the other products of the range which are developed with a similar technology.
Products covered	AP86XX Series
Functional unit	Establish, support and interrupt for 10 years rated currents in normal conditions of the circuit characterized by the current 16/20A, for the operating voltage 208/230V, across 24 sockets.



Constituent materials

Reference product mass	8820 g including the product, its packaging and additional elements and accessories
------------------------	---



Plastics	9,8%
Metals	45,1%
Others	45,0%



Substance assessment

Products of this range are designed in conformity with the requirements of the European RoHS Directive 2011/65/EU (RoHS2) and EU Delegated Directive (EU) 2015/863 and do not contain, or only contain in the authorised proportions, lead, mercury, cadmium, hexavalent chromium, flame retardants (polybrominated biphenyls - PBB, polybrominated diphenyl ethers - PBDE) or phthalates (Bis(2-ethylhexyl) phthalate - DEHP, Butyl benzyl phthalate - BBP, Dibutyl phthalate -DBP, Diisobutyl phthalate - DIBP as mentioned in the Directive

As the products of the range are designed in accordance with the RoHS Directive (European Directive 2002/95/EC of 27 January 2003), they can be incorporated without any restriction in an assembly or an installation subject to this Directive.

Details of ROHS and REACH substances information are available on the Schneider-Electric Green Premium website

<http://www2.schneider-electric.com/sites/corporate/en/products-services/green-premium/green-premium.page>



Additional environmental information

The Rack PDU 2G, Metered by Outlet with Switching with Power Cord presents the following relevant environmental aspects

Manufacturing	Manufactured at a production site complying with the regulations
Distribution	Weight and volume of the packaging optimized, based on the European Union's packaging directive Packaging weight is 1740,7 g, consisting of cardboard (65%), paper (9%), polyethylene (20%), other plastics (6%) Product distribution optimised by setting up local distribution centres
Installation	The product does not require any special installation materials or operations. Installation is to be performed by qualified personnel.
Use	The product does not require special maintenance operations.
End of life	End of life optimized to decrease the amount of waste and allow recovery of the product components and materials This product contains lithium metal coin battery (3g), electronic cards >10cm ² (2500g) and an external electric cable (360g) that should be separated from the stream of waste so as to optimize end-of-life treatment. The location of these components and other recommendations are given in the End of Life Instruction document which is available on the Schneider-Electric Green Premium website http://www2.schneider-electric.com/sites/corporate/en/products-services/green-premium/green-premium.page Recyclability potential: 60% Based on "ECO'DEEE recyclability and recoverability calculation method" (version V1, 20 Sep. 2008 presented to the French Agency for Environment and Energy Management: ADEME).




Environmental impacts

Reference life time	10 years			
Product category	Combination of functions			
Installation elements	Transportation and disposal of packaging are accounted for during installation. No special installation components needed.			
Use scenario	Weighted average loss = 8.7W, 100% of the time			
Geographical representativeness	The product can be used in all regions, but the majority of the product is deployed in Europe			
Technological representativeness	The means of material production, processing and transport modeled are representative of the technologies used in production.			
Energy model used	Manufacturing	Installation	Use	End of life
	Energy model used: China, France and EU-27	Electricity grid mix; AC; consumption mix, at consumer; < 1kV; EU-27	Electricity grid mix; AC; consumption mix, at consumer; < 1kV; EU-27	Electricity grid mix; AC; consumption mix, at consumer; < 1kV; EU-27

Compulsory indicators		Rack PDU 2G, Metered by Outlet with Switching with Power Cord - AP8659					
Impact indicators	Unit	Total	Manufacturing	Distribution	Installation	Use	End of Life
Contribution to mineral resources depletion	kg Sb eq	2,70E-02	2,69E-02	0*	0*	3,24E-05	0*
Contribution to the soil and water acidification	kg SO ₂ eq	2,01E+00	4,44E-01	5,20E-03	4,66E-04	1,56E+00	3,43E-03
Contribution to water eutrophication	kg PO ₄ ³⁻ eq	1,80E-01	8,29E-02	1,20E-03	2,44E-04	9,40E-02	1,52E-03
Contribution to global warming	kg CO ₂ eq	5,37E+02	1,58E+02	1,14E+00	1,15E-01	3,73E+02	4,57E+00
Contribution to ozone layer depletion	kg CFC11 eq	3,98E-05	1,53E-05	0*	0*	2,43E-05	1,71E-07
Contribution to photochemical oxidation	kg C ₂ H ₄ eq	1,28E-01	4,21E-02	3,71E-04	3,52E-05	8,56E-02	3,07E-04
Resources use	Unit	Total	Manufacturing	Distribution	Installation	Use	End of Life
Net use of freshwater	m ³	1,36E+03	9,50E+00	0*	0*	1,35E+03	0*
Total Primary Energy	MJ	1,04E+04	2,92E+03	1,61E+01	1,42E+00	7,46E+03	1,59E+01

- Rack PDU 2G, Metered by Outlet with Switching with Power Cord



Optional indicators		Rack PDU 2G, Metered by Outlet with Switching with Power Cord - AP8659					
Impact indicators	Unit	Total	Manufacturing	Distribution	Installation	Use	End of Life
Contribution to fossil resources depletion	MJ	6,30E+03	2,03E+03	1,60E+01	1,55E+00	4,24E+03	1,46E+01
Contribution to air pollution	m³	3,49E+04	1,87E+04	4,84E+01	7,61E+00	1,61E+04	1,12E+02
Contribution to water pollution	m³	3,36E+04	1,74E+04	1,87E+02	1,60E+01	1,54E+04	5,88E+02
Resources use	Unit	Total	Manufacturing	Distribution	Installation	Use	End of Life
Use of secondary material	kg	1,55E+00	1,55E+00	0*	0*	0*	0*
Total use of renewable primary energy resources	MJ	9,99E+02	5,02E+01	0*	0*	9,48E+02	0*
Total use of non-renewable primary energy resources	MJ	9,41E+03	2,87E+03	1,61E+01	1,41E+00	6,51E+03	1,59E+01
Use of renewable primary energy excluding renewable primary energy used as raw material	MJ	9,73E+02	2,50E+01	0*	0*	9,48E+02	0*
Use of renewable primary energy resources used as raw material	MJ	2,52E+01	2,52E+01	0*	0*	0*	0*
Use of non renewable primary energy excluding non renewable primary energy used as raw material	MJ	9,34E+03	2,80E+03	1,61E+01	1,41E+00	6,51E+03	1,59E+01
Use of non renewable primary energy resources used as raw material	MJ	7,25E+01	7,25E+01	0*	0*	0*	0*
Use of non renewable secondary fuels	MJ	0,00E+00	0*	0*	0*	0*	0*
Use of renewable secondary fuels	MJ	0,00E+00	0*	0*	0*	0*	0*
Waste categories	Unit	Total	Manufacturing	Distribution	Installation	Use	End of Life
Hazardous waste disposed	kg	1,35E+02	1,21E+02	0*	0*	1,95E-01	1,33E+01
Non hazardous waste disposed	kg	1,46E+03	6,33E+01	0*	3,68E-01	1,39E+03	0*
Radioactive waste disposed	kg	9,49E-01	1,92E-02	0*	0*	9,30E-01	9,81E-05
Other environmental information	Unit	Total	Manufacturing	Distribution	Installation	Use	End of Life
Materials for recycling	kg	6,48E+00	6,29E-01	0*	1,41E+00	0*	4,44E+00
Components for reuse	kg	0,00E+00	0*	0*	0*	0*	0*
Materials for energy recovery	kg	1,09E+00	0*	0*	0*	0*	1,09E+00
Exported Energy	MJ	4,08E-03	3,84E-04	0*	3,70E-03	0*	0*

* represents less than 0.01% of the total life cycle of the reference flow

Life cycle assessment performed with EIME version EIME v5.8.0, database version 2018-11 in compliance with ISO14044.

The use phase is the life cycle phase which has the greatest impact on the majority of environmental indicators (based on compulsory indicators).

According to this environmental analysis, proportionality rules may be used to evaluate the impacts of other products of this range.

The environmental indicators of other products in this family may be proportional extrapolated based on relationships between an amount of a key parameter of the product as compared to the amount of that key parameter within the reference product. Proportionality rules are based on the following key parameters: Manufacturing phase impacts - total mass of product (excluding packaging). Distribution phase impacts - total mass of product (including packaging). Installation phase impacts - mass of packaging. Use phase impacts - life time energy use. End of Life impacts - the product mass (excluding packaging).

Please note that the values given above are only valid within the context specified and cannot be used directly to draw up the environmental assessment of an installation.

Verifier accreditation N° VH-08 Date of issue 01/2019	Drafting rules PCR-ed3-EN-2015 04 02 Supplemented by PSR-0005-ed2-EN-2016 03 29 Validity period 6 years
<i>Independent verification of the declaration and data, in compliance with ISO 14025 : 2010</i> Internal X External	
<i>The PCR review was conducted by a panel of experts chaired by Philippe Osset (SOLINNEN)</i> <i>PEP are compliant with XP C08-100-1 :2014</i> <i>The elements of the present PEP cannot be compared with elements from another program.</i> <i>Document in compliance with ISO 14025 : 2010 « Environmental labels and declarations. Type III environmental declarations »</i>	

Schneider Electric Industries SAS

Country Customer Care Center
<http://www.schneider-electric.com/contact>

35, rue Joseph Monier
CS 30323
F- 92506 Rueil Malmaison Cedex
RCS Nanterre 954 503 439
Capital social 896 313 776 €

www.schneider-electric.com