## XS7J1A1NAL2

inductive sensor XS7 8x22x8 - PBT - Sn2.5mm - 12..24VDC - cable 2m





#### Main

Range of product	OsiSense XS
Series name	General purpose
Sensor type	Inductive proximity sensor
Device application	-
Sensor name	XS7
Sensor design	Flat form 8 x 22 x 8
Size	8 mm
Body type	Fixed
Detector flush mounting acceptance	Flush mountable
Material	Plastic
Enclosure material	PBT
Type of output signal	Discrete
Wiring technique	3-wire
Discrete output function	1 NO
Output circuit type	DC
Discrete output type	NPN
Electrical connection	cable
Cable length	6.56 ft (2 m)
[Us] rated supply voltage	1224 V DC reverse polarity protection
Switching capacity in mA	<= 100 mA DC overload and short-circuit protection
IP degree of protection	IP67 IEC 60529

### Complementary

Complementary	
Detection face	Frontal
Front material	PBT
Operating zone	0.000.08 in (02 mm)
Differential travel	115% of Sr
Cable composition	3 x 0.11 mm²
Wire insulation material	PvR
Status LED	Output state 1 LED yellow)
Supply voltage limits	1036 V DC
Switching frequency	<= 2000 Hz
Maximum voltage drop	<2 V closed)
Current consumption	<= 10 mA no-load
Maximum delay first up	5 ms
Maximum delay response	0.1 ms
Maximum delay recovery	0.1 ms
Marking	CE
Depth	0.31 in (8 mm)
Height	0.87 in (22 mm)
Maximum Width	0.31 in (8 mm)

### Environment

Environment		

## Ordering and shipping details

Category	22486 - SENSORS, PROXIMITY
Discount Schedule	DS2
GTIN	00785901484769
Nbr. of units in pkg.	1
Package weight(Lbs)	0.12 lb(US) (0.05 kg)
Returnability	No
Country of origin	ID

# Packing Units

Package 1 Height	0.420 dm	
Package 1 width	0.950 dm	
Package 1 Length	1.320 dm	

### Offer Sustainability

Sustainable offer status	Green Premium product	
California proposition 65	WARNING: This product can expose you to chemicals including: Diisor phthalate (DINP), which is known to the State of California to cause ca and Di-isodecyl phthalate (DIDP), which is known to the State of Califor to cause birth defects or other reproductive harm. For more information www.P65Warnings.ca.gov	
REACh Regulation	<sup>™</sup> REACh Declaration	
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) <sup>™</sup> EU RoHS Declaration	
Mercury free	Yes	
RoHS exemption information	₫Yes	
Environmental Disclosure	Product Environmental Profile	

### Contractual warranty

Warranty	18 months	