

Product data sheet

Characteristics

8910DPA92V02

Contactor, Definite Purpose, 90A, 2 pole, 20 HP at 230 VAC, 1 phase, 110/120 VAC 50/60 Hz coil, open



Main

Product or component type	Definite Purpose Contactor
Line Rated Current	90 A
Number of Poles	2P
Pole contact composition	2 NO
Range of product	DPA

Complementary

Maximum Horse Power Rating	7.5 Hp 115 V AC, 1 phase 20 hp 230 V AC, 1 phase
Locked rotor rated current	540 A 277 V AC 450 A 460 V AC 360 A 575 V AC
[Ue] rated operational voltage	600 V AC
[Uc] control circuit voltage	120 V AC 60 Hz 110 V AC 50 Hz
Phase	1 phase
Electrical connection	Quick connect terminals Box lugs

Environment

Product certifications	UL Recognized CSA
------------------------	----------------------

Ordering and shipping details

Category	21349 - 8910 DPA 9_(90 AMP)
Discount Schedule	CP1B
GTIN	00785901118381
Nbr. of units in pkg.	1
Package weight(Lbs)	3.4 lb(US) (1.54 kg)
Returnability	Yes
Country of origin	CN

Packing Units

Package 1 Height	6.10 in (15.494 cm)
Package 1 width	5.60 in (14.224 cm)
Package 1 Length	7.00 in (17.780 cm)

Offer Sustainability

REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration

Contractual warranty

Warranty	18 months
----------	-----------