



Overview

Lead time	Usually in Stock
-----------	------------------

General

Provided equipment	CD with software Documentation CD Installation guide Integrated network management Removable support feet Temperature probe
Product web sub-family	High density
Number of tare power	77 W
Number of power module free slots	0
Number of power module filled slots	0
Redundant	No
UPS size	S

Physical

Cable length	10 ft (3.05 m)
Color	Black
Depth	28.31 in (71.9 cm)
Height	17.01 in (43.2 cm)
Mounting position	Vertical
Mounting preference	No preference
Net Weight	248.00 lb(US) (112.49 kg)
Mounting mode	Rack-mounted with kit
Two post mountable	0
USB compatible	Yes
Maximum Width	10.20 in (25.9 cm)

Input

Input Frequency	40...70 Hz auto-sensing
Plug standard	NEMA L6-30P
Efficiency at full load	100...275 V adjustable (half load) 160...275 V
Other Input Voltages	240 V
Nominal Input Voltage	208 V

Output

Kw Rating	4800 W
Max Configurable Power (Watts)	4800 W
Harmonic distortion	Less than 2%
Output frequency	50/60 Hz +/- 3 Hz sync to mains
Other Output Voltages	240 V
Topology	Double Conversion Online
Waveform Type	Sine wave
Nb of power socket outlets	8 NEMA 5-20R 4 NEMA L6-20R 2 NEMA L6-30R 1 NEMA L14-30R
Bypass type	Internal Bypass (Automatic and Manual)
Curve equation	Efficiency
Curve fixed loss	0.0136
Curve load maximum	100 %
Curve load minimum	2 %
Curve proportional loss	0.0223
Curve square loss	0.0244
Curve X-axis maximum	100 %
Curve test cond ID	Curve fit of data measured in accordance with the ENERGY STAR Test Method for Uninterruptible Power Supplies. All measurements taken in normal mode(s), at typical environmental conditions, with 240V/60Hz electrical input and balanced resistive load (PF = 1.0) output.
Curve X-axis minimum	0 %
Curve X-axis title	Load
Curve X-axis units	Percentage
Curve Y-axis maximum	100 %
Curve Y-axis minimum	50 %
Curve Y-axis title	Efficiency
Curve Y-axis units	Percentage
Graph display	1
Output voltage	120 V 208 V
Maximum configurable power in VA	5000 VA
Rated power in VA	5000 VA

Conformance

Product certifications	ENERGY STAR V2.0 (USA)
Standards	CSA C22.2 No.107.3-05 FCC Part 15 class A UL 1778

Environmental

Ambient air temperature for operation	32...104 °F (0...40 °C)
Relative humidity	0...95 % non-condensing
Operating altitude	0...10000 ft
Ambient air temperature for storage	5...113 °F (-15...45 °C)
Storage altitude	0...50000 ft (0.00...15240.00 m)
Acoustic level	55 dBA
Heat dissipation	1047 Btu/h
Show note OP temperature	No
IP degree of protection	IP20

Batteries & Runtime

Battery type	Lead-Acid battery
Included Battery Modules	0
Battery Slots Empty	0
Typical recharge time	1.5 h
Liquid Electrolyte Value	0
Battery voltage	192V
Battery curve	D
Battery Charge Power (Watts)	556 W rated
Battery power in VAh	840 VAh runtime
Battery life	3...5 year(s)
Battery option	SRT192BP 1 2520 VAh SRT192BP 2 4200 VAh SRT192BP 3 5880 VAh SRT192BP 4 7560 VAh SRT192BP 5 9240 VAh SRT192BP 6 10920 VAh SRT192BP 8 14600 VAh SRT192BP 10 17640 VAh
Extendable Run Time	1

Communications & Management

Free slots	1
Control panel	Multi-function LCD status and control console
Audible Alarm	Audible and visible alarms prioritized by severity
Emergency Power Off (EPO)	Yes

Surge Protection and Filtering

Surge energy rating	480 J
---------------------	-------







Ordering and shipping details

Package weight(Lbs)	281.99 lb(US) (127.91 kg)
---------------------	---------------------------

Packing Units

Package 1 Height	26.69 in (67.8 cm)
Package 1 width	24.02 in (61 cm)
Package 1 Length	38.58 in (98 cm)
Number of Units in Package 3	3

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
Energy Star	 ENERGY STAR UPS V1.0 (USA)
REACH Regulation	 REACH Declaration
EU RoHS Directive	Compliant  EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	 Yes
Environmental Disclosure	 Product Environmental Profile
Circularity Profile	 End Of Life Information
Optimized Energy Efficiency	Energy efficient product

Contractual warranty

Warranty	3 years repair or replace (excluding battery) and 2 years for battery
----------	---