D326NR

Safety switch, general duty, fusible, 600A, 3 poles, 150 hp, 240 VAC, NEMA 3R, neutral factory installed





Main

Product	Single Throw Safety Switch
Current Rating	600 A
Certifications	UL listed file E2875
Enclosure Rating	NEMA 3R
Disconnect Type	Fusible disconnect switch
Factory Installed Neutral	Neutral (factory installed)
Short Circuit Current Rating	100 kA maximum depending on fuse H, K, J or R
Mounting Type	Surface
Number of Poles	3
Electrical Connection	Lugs
Duty Rating	General duty
Voltage Rating	240 V AC
Wire Size	AWG 4500 kcmil aluminium/copper

Complementary

Complementary		
Maximum Horse Power Rating	75 Hp 240 V AC 60 Hz 3 phase NEC 240.6 150 hp 240 V AC 60 Hz 3 phase NEC 430.52	
Maximum Width	25.13 in (638.30 mm)	
Height	49.13 in (1247.90 mm)	
Depth	8.88 in (225.55 mm)	
Tightening torque	450 lbf.in (50.84 N.m) AWG 4500 kcmil)	

Ordering and shipping details

Category	00107 - D & DU SW,NEMA3R, 400-600A
Discount Schedule	DE1A
GTIN	00785901461661
Nbr. of units in pkg.	1
Package weight(Lbs)	117 lb(US) (53.07 kg)
Returnability	Yes
Country of origin	MX

Packing Units

Unit Type of Package 1	PCE	
Package 1 Height	0.94 ft (0.287 m)	
Package 1 width	2.18 ft (0.665 m)	
Package 1 Length	4.27 ft (1.3 m)	

Offer Sustainability

Warranty

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	☑ REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Compliant EEU RoHS Declaration
Mercury free	Yes
RoHS exemption information	₫ _{Yes}
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
PVC free	Yes
Halogen content performance	Halogen free plastic parts product

18 months