# Product data sheet Characteristics

## NSYS3DC12840

WM S3DC plain door w/o plain chassis, w/o cable gland plate. H1200xW800xD400mm.



Main	
Range	Spacial
Product name	Spacial S3DC
Application	Multi-purpose
Category	Compact enclosure
Enclosure nominal height	47.24 in (1200 mm)
Enclosure nominal width	31.50 in (800 mm)
Enclosure nominal depth	15.75 in (400 mm)
Door type	Solid
Mounting plate description	Without mounting plate
Type of gland plate	Without gland plate
Installation accessory type	Wall-mounting
Device composition	1 body 1 door 1 lock

#### Complementary

Body type	Gutter-shaped front profile double sheet thickness
Body type	·
	Single piece body
Number of doors	Front face: 1 door(s)
Door opening side	Reversible 120 °)
Lock type	3 points lock, screw driver insert
Accessibility for operation	Front
Removable parts	Door by hinges
Material	Steel
Surface finish	Epoxy-polyester powder
Color	Gray RAL 7035)
Standards	IEC 62208
Product certifications	UL
Net weight	110.23 lb(US) (50 kg)

#### Environment

IP degree of protection	IP66 IEC 60529
IK degree of protection	IK10 IEC 62262

#### Ordering and shipping details

Category	80034 - ENCLOSURE SYSTEMS WALL MOUNT METAL
Discount Schedule	ES1
GTIN	00785901662884
Nbr. of units in pkg.	1
Package weight(Lbs)	107.8 lb(US) (48.90 kg)
Returnability	Yes
Country of origin	FR

## Packing Units

Package 1 Height	50.79 in (1290.000 mm)
Package 1 width	32.48 in (825.000 mm)
Package 1 Length	17.91 in (455.000 mm)

### Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EVEL RoHS  Declaration
Mercury free	Yes
RoHS exemption information	₫Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile

#### Contractual warranty

Warranty	18 months
vvaiiaiily	10 1110111115
•	