



## Main

Range of product	Harmony XVR
Product or component type	Prewired rotating mirror beacon
Sound signalling	Without
Device short name	XVR
Mounting diameter	5.12 in (130 mm)
IP degree of protection	IP66 conforming to IEC 60529 IP67 conforming to IEC 60529
[Us] rated supply voltage	24 V AC/DC
Light source	High luminosity LED, red

## Complementary

Material	ABS (acrylonitrile butadiene-styrene) body part PC globe
CAD overall width	5.12 in (130 mm)
CAD overall depth	5.12 in (130 mm)
Net Weight	1.81 lb(US) (0.82 kg)
Marking	CE
Product mounting	By 3 M6 screws
[Uimp] rated impulse withstand voltage	0.8 kV
Current consumption	125 mA
Flashing frequency	2.7 Hz
Clamping connection capacity	1.25 mm <sup>2</sup>
AWG gauge	AWG 18
Cable length	15.75 in (400 mm)

## Environment

Standards	EN/IEC 61000-6-2 EN/IEC 61000-6-4
Protective treatment	TC
Ambient air temperature for storage	-31...158 °F (-35...70 °C)
Ambient air temperature for operation	-22...122 °F (-30...50 °C)
Electrical shock protection class	Class II IEC 61140

## Ordering and shipping details

Category	22617 - XVC TOWER LIGHTS
Discount Schedule	XV
GTIN	00785901944805
Nbr. of units in pkg.	1
Package weight(Lbs)	2.49 lb(US) (1.13 kg)
Returnability	No
Country of origin	ID

## Packing Units

Unit Type of Package 1	PCE
Package 1 Height	10.43 in (26.5 cm)
Package 1 width	7.36 in (18.7 cm)
Package 1 Length	7.40 in (18.8 cm)
Unit Type of Package 2	S04
Number of Units in Package 2	6
Package 2 Weight	17.63 lb(US) (7.996 kg)
Package 2 Height	11.81 in (30 cm)
Package 2 width	15.75 in (40 cm)
Package 2 Length	23.62 in (60 cm)

## Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	<a href="#">End Of Life Information</a>



## Contractual warranty

Warranty	18 months
----------	-----------

Rotating Mirror Beacon

Dimensions

mm  
in.



---

Rotating Mirror Beacon

---

Panel Cut-out

