



## Main

Product	Single Throw Safety Switch
Current Rating	100 A
Number of Poles	4
Voltage Rating	600 V AC/DC
Wire Size	AWG 12...AWG 1/0 aluminium AWG 14...AWG 1/0 copper
Disconnect Type	Fusible disconnect
Short Circuit Current Rating	10 KA H or K 200 kA R, J or L
Mounting Type	Surface
Factory Installed Neutral	None
Electrical Connection	Lugs
Duty Rating	Heavy duty
Certifications	UL listed file E2875
Enclosure Rating	NEMA 1 steel

## Complementary

Maximum Horse Power Rating	25 Hp 480 V AC 50...60 Hz 2 phases NEC 240.6 60 Hp 480 V AC 50...60 Hz 2 phases NEC 430.52 30 Hp 600 V AC 50...60 Hz 2 phases NEC 240.6 75 Hp 600 V AC 50...60 Hz 2 phases NEC 430.52 20 Hp at 250 V DC 30 hp 600 V DC
Maximum Width	16.13 in (409.70 mm)
Height	20.5 in (520.70 mm)
Depth	6.85 in (173.99 mm)
Tightening torque	5.65 N.M (AWG 1...AWG 3/0) 5.08 N.M (AWG 6...AWG 4) 4.52 N.M for 8.367 mm <sup>2</sup> (AWG 8) 3.95 N.m for 2.06...5.261 mm <sup>2</sup> (AWG 14...AWG 10)

## Ordering and shipping details

Category	00008 - H&HU SW,2&3P,N1,30-200A
Discount Schedule	DE1
GTIN	00785901482499
Nbr. of units in pkg.	1
Package weight(Lbs)	38.24 lb(US) (17.35 kg)
Returnability	Yes
Country of origin	US

## Packing Units

Unit Type of Package 1	PCE
Package 1 Height	7.10 in (18.034 cm)
Package 1 width	16.80 in (42.672 cm)
Package 1 Length	25.70 in (65.278 cm)

## Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>
REACH Regulation	<a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
PVC free	Yes

## Contractual warranty

Warranty	18 months
----------	-----------