



## Main

|                           |                 |
|---------------------------|-----------------|
| Range                     | PowerPact       |
| Product name              | PowerPact B     |
| Device short name         | BD 015          |
| Product or component type | Circuit breaker |
| Device application        | Distribution    |

## Complementary

|                                        |                                                                                                                                                                                                                               |
|----------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Line Rated Current                     | 15 A                                                                                                                                                                                                                          |
| Number of Poles                        | 3P                                                                                                                                                                                                                            |
| Control type                           | Toggle                                                                                                                                                                                                                        |
| Breaking capacity code                 | D                                                                                                                                                                                                                             |
| Breaking capacity                      | 25 KA 208Y/120 V AC 50/60 Hz UL 489<br>25 KA 240 V AC 50/60 Hz UL 489<br>18 KA 480/277 V AC 50/60 Hz UL 489<br>18 KA 480 V AC 50/60 Hz UL 489<br>14 KA 600Y/347 V AC 50/60 Hz UL 489<br>10 KA 250 V DC UL 489                 |
| [Ue] rated operational voltage         | 525 V AC 50/60 Hz UL 489                                                                                                                                                                                                      |
| [Ics] rated service breaking capacity  | 25 KA at 220...240 V AC 50/60 Hz conforming to IEC 60947-2<br>14 KA 500...525 V AC 50/60 Hz IEC 60947-2<br>18 KA at 380...415 V AC 50/60 Hz conforming to IEC 60947-2<br>18 KA at 440 V AC 50/60 Hz conforming to IEC 60947-2 |
| [Uimp] rated impulse withstand voltage | 8 kV IEC 60947-2                                                                                                                                                                                                              |
| [Ui] rated insulation voltage          | 800 V IEC 60947-2                                                                                                                                                                                                             |
| Trip unit technology                   | Thermal-magnetic                                                                                                                                                                                                              |
| Suitability for isolation              | Yes IEC 60947-2                                                                                                                                                                                                               |
| Utilisation category                   | Category A                                                                                                                                                                                                                    |
| Mechanical durability                  | 20000 cycles IEC 947-1 Annex K ed 5.2                                                                                                                                                                                         |
| Electrical durability                  | 10000 cycles IEC 947-1 Annex K ed 5.2 440 V In                                                                                                                                                                                |
| Connection pitch                       | 1.06 in (27 mm)                                                                                                                                                                                                               |
| Local signalling                       | Presence of auxiliary contacts flag green)                                                                                                                                                                                    |
| Mounting mode                          | I-Line                                                                                                                                                                                                                        |
| Electrical connection                  | I-Line connection line<br>Lugs load                                                                                                                                                                                           |
| AWG gauge                              | AWG 14...AWG 2/0 aluminium/copper                                                                                                                                                                                             |
| Mounting height                        | 4.49 in (114 mm)                                                                                                                                                                                                              |
| Tightening torque                      | 31.86...38.94 Lbf.in (3.6...4.4 N.m) 0.00...0.01 in <sup>2</sup> (2.5...6 mm <sup>2</sup> ) AWG 14...AWG 10)<br>44.25...54.87 lbf.in (5...6.2 N.m) 0.02...0.11 in <sup>2</sup> (10...70 mm <sup>2</sup> ) AWG 8...AWG 2/0)    |
| Number of slots                        | 1 auxiliary switch OF plug-in)<br>1 voltage release MN or MX plug-in)<br>1 alarm switch SD plug-in)                                                                                                                           |
| Power wire stripping length            | 0.79 in (20 mm)                                                                                                                                                                                                               |
| Color                                  | Gray RAL 7016)                                                                                                                                                                                                                |
| 9 mm pitches                           | 9                                                                                                                                                                                                                             |

|                           |                        |
|---------------------------|------------------------|
| Height                    | 5.39 in (137 mm)       |
| Maximum Width             | 3.19 in (81 mm)        |
| Depth                     | 3.50 in (89 mm)        |
| Net Weight                | 2.90 lb(US) (1.315 kg) |
| Quantity per set          | Set of 1               |
| Phase connection          | ABC                    |
| Continuous current rating | 80 %                   |

## Environment

|                                       |                                                                                                       |
|---------------------------------------|-------------------------------------------------------------------------------------------------------|
| Quality labels                        | CE                                                                                                    |
| Standards                             | EN/IEC 60947-5-1<br>GB 14048.2<br>UL 489<br>CSA C22.2 No 5<br>EN/IEC 60947-2<br>NEMA AB1<br>NMJ J-266 |
| Product certifications                | UL<br>IEC<br>CCC<br>EAC<br>CSA<br>NOM                                                                 |
| IP degree of protection               | Front cover IP40 IEC 60529                                                                            |
| IK degree of protection               | IK07 conforming to IEC 62262                                                                          |
| Pollution degree                      | 3 IEC 60947-1                                                                                         |
| Ambient air temperature for operation | -13...158 °F (-25...70 °C)                                                                            |
| Ambient air temperature for storage   | -58...185 °F (-50...85 °C)                                                                            |
| Operating altitude                    | < 6561.68 ft (2000 m) without derating<br>5000 m with derating                                        |

## Ordering and shipping details

|                       |                            |
|-----------------------|----------------------------|
| Category              | 01133 - BDA I-LINE BREAKER |
| Discount Schedule     | DE2                        |
| GTIN                  | 03606481152480             |
| Nbr. of units in pkg. | 1                          |
| Package weight(Lbs)   | 3.8 lb(US) (1.72 kg)       |
| Returnability         | Yes                        |
| Country of origin     | MX                         |

## Packing Units

|                  |                      |
|------------------|----------------------|
| Package 1 Height | 4.70 in (11.938 cm)  |
| Package 1 width  | 5.90 in (14.986 cm)  |
| Package 1 Length | 10.80 in (27.432 cm) |

## Offer Sustainability

|                            |                                                                                                                                                                                                                                                                                                                                    |
|----------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Sustainable offer status   | Green Premium product                                                                                                                                                                                                                                                                                                              |
| California proposition 65  | WARNING: This product can expose you to chemicals including: DINP, which is known to the State of California to cause cancer, and DIDP, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a> |
| REACH Regulation           |  <a href="#">REACH Declaration</a>                                                                                                                                                                                                              |
| EU RoHS Directive          | Compliant  <a href="#">EU RoHS Declaration</a>                                                                                                                                                                                                  |
| Mercury free               | Yes                                                                                                                                                                                                                                                                                                                                |
| RoHS exemption information |  <a href="#">Yes</a>                                                                                                                                                                                                                            |
| China RoHS Regulation      |  <a href="#">China RoHS Declaration</a>                                                                                                                                                                                                         |
| Environmental Disclosure   |  <a href="#">Product Environmental Profile</a>                                                                                                                                                                                                  |

|                             |                                                                                                                              |
|-----------------------------|------------------------------------------------------------------------------------------------------------------------------|
| WEEE                        | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins. |
| PVC free                    | Yes                                                                                                                          |
| Halogen content performance | Halogen free product                                                                                                         |