# QDL32225

Trip unit technology

PowerPact Q - molded case circuit breaker - 3-pole - 25 kA - 240 V - 225 A





Main		
Product or component type	Circuit breaker	
Range of product	PowerPact Q	

Thermal-magnetic

#### Complementary

Line Rated Current	225 A	
[Ue] rated operational voltage	240 V AC	
Number of poles	3	
Breaking capacity	25 kA 240 V AC	
Continuous current rating	80 %	
Breaking capacity code	D	
Mounting mode	Unit mount	
Electrical connection	Lugs load AWG 4300 kcmil aluminium/copper Lugs line AWG 4300 kcmil aluminium/copper	
Magnetic hold current	1200 A	
Magnetic tripping current	2400 A	
Height	6.47 in (164.34 mm)	
Maximum Width	4.5 in (114.30 mm)	
Depth	3.93 in (99.82 mm)	
Tightening torque	247.82 lbf.in (28 N.m) 0.040.23 in² (25150 mm²) AWG 4300 kcmil)	

#### Environment

Product certifications	UL Listed IEC CSA
	CSA

#### Ordering and shipping details

Category	00023 - QO,Q2L 3P ENCL & BREAKERS	
Discount Schedule	DE2	
GTIN	00785901672470	
Nbr. of units in pkg.	1	
Package weight(Lbs)	4.75 lb(US) (2.15 kg)	
Returnability	Yes	
Country of origin	MX	

## **Packing Units**

· coming come		
Unit Type of Package 1	PCE	
Package 1 Height	6.30 in (16.002 cm)	
Package 1 width	6.20 in (15.748 cm)	
Package 1 Length	9.80 in (24.892 cm)	
Unit Type of Package 2	PAL	
Number of Units in Package 2	200	
Package 2 Weight	2205.00 lb(US) (1000.17 kg)	
Package 2 Height	40.00 in (101.6 cm)	
Package 2 width	40.00 in (101.6 cm)	
Package 2 Length	48.00 in (121.92 cm)	

# Offer Sustainability

Sustainable offer status	Green Premium product	
California proposition 65	WARNING: This product can expose you to chemicals including: DINP, which is known to the State of California to cause cancer, and DIDP, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov	
REACh Regulation	REACh Declaration	
REACh free of SVHC	Yes	
EU RoHS Directive	Compliant EEU RoHS Declaration	
Mercury free	Yes	
RoHS exemption information	€Yes	
China RoHS Regulation	China RoHS Declaration	
Environmental Disclosure	Product Environmental Profile	
PVC free	Yes	
Halogen content performance	Halogen free product	

## Contractual warranty

14/	40	
Warranty	18 months	
• • •		