



## Main

|                           |                            |
|---------------------------|----------------------------|
| Product or component type | Single Throw Safety Switch |
| Series name               | General duty               |

## Complementary

|                                |  |
|--------------------------------|--|
| Line Rated Current             | 60 A   |
| Device composition             | Neutral (factory installed)  |
| Disconnecter device type       | Fusible disconnect   |
| Short-circuit current          | 100 kA maximum cartridge   |
| Device mounting                | Surface  |
| Number of poles                | 3  |
| Electrical connection          | Lugs   |
| [Ue] rated operational voltage | 120/240 V AC   |
| AWG gauge                      | AWG 14...AWG 3 copper or aluminium   |
| Maximum Horse Power Rating     | 7.5 Hp 240 V AC 50...60 Hz 1 phase NEC 240.6<br>15 Hp 240 V AC 50...60 Hz 3 phase NEC 240.6<br>15 Hp 240 V AC 50...60 Hz 1 phase NEC 430.52<br>30 hp 240 V AC 50...60 Hz 3 phase NEC 430.52  |
| Maximum Width                  | 7.45 in (189.23 mm)  |
| Height                         | 14.6 in (370.84 mm)  |
| Depth                          | 4.87 in (123.70 mm)  |
| Tightening torque              | 35 Lbf.In (3.95 N.m) 0.00...0.01 in <sup>2</sup> (2.08...5.26 mm <sup>2</sup> ) AWG 14...AWG 10)<br>45 Lbf.In (5.08 N.m) 0.01 in <sup>2</sup> (8.37 mm <sup>2</sup> ) AWG 8)<br>45 Lbf.In (5.08 N.m) 0.02...0.03 in <sup>2</sup> (12.3...21.12 mm <sup>2</sup> ) AWG 6...AWG 4)<br>50 lbf.in (5.65 N.m) 0.04 in <sup>2</sup> (26.67 mm <sup>2</sup> ) AWG 3) |

## Environment

|                           |                         |
|---------------------------|-------------------------|
| Product certifications    | CSA                     |
| NEMA degree of protection | NEMA 1 galvanized steel |

## Ordering and shipping details

|                       |                                   |
|-----------------------|-----------------------------------|
| Category              | 00154 - CD&CDU CANADA SW NON-NEGO |
| Discount Schedule     | DE1A                              |
| GTIN                  | 00785901404934                    |
| Nbr. of units in pkg. | 1                                 |
| Package weight(Lbs)   | 8.05 lb(US) (3.65 kg)             |
| Returnability         | Yes                               |
| Country of origin     | US                                |

## Packing Units

|                  |                      |
|------------------|----------------------|
| Package 1 Height | 5.30 in (13.462 cm)  |
| Package 1 width  | 7.80 in (19.812 cm)  |
| Package 1 Length | 16.20 in (41.148 cm) |

## Offer Sustainability

|                            |   |
|----------------------------|---|
| Sustainable offer status   | Green Premium product   |
| California proposition 65  | WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a> |
| REACH Regulation           | <a href="#">REACH Declaration</a>   |
| REACH free of SVHC         | Yes   |
| EU RoHS Directive          | Compliant <a href="#">EU RoHS Declaration</a>   |
| Mercury free               | Yes   |
| RoHS exemption information | <a href="#">Yes</a>   |
| China RoHS Regulation      | <a href="#">China RoHS Declaration</a>  |
| Environmental Disclosure   | <a href="#">Product Environmental Profile</a>   |
| PVC free                   | Yes   |

## Contractual warranty

|          |           |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|