



Main

| | |
|------------------------------|---|
| Product | Single Throw Safety Switch |
| Current Rating | 800 A |
| Number of Poles | 3 |
| Voltage Rating | 250 V DC 240 V AC |
| Wire Size | AWG 3/0...750 kcmil copper or aluminium |
| Disconnect Type | Fusible disconnect |
| Short Circuit Current Rating | 200 kA maximum L |
| Mounting Type | Surface |
| Factory Installed Neutral | None |
| Electrical Connection | Lugs |
| Duty Rating | Heavy duty |
| Certifications | UL listed file E2875 |
| Enclosure Rating | NEMA 3R galvanized steel |

Complementary


| | |
|----------------------------|--|
| Maximum Horse Power Rating | 50 Hp 240 V AC 50...60 Hz 1 phase NEC 240.6 100 Hp 240 V AC 50...60 Hz 3 phase NEC 240.6 250 Hp 240 V AC 50...60 Hz 3 phase NEC 430.52 50 hp 250 V DC |
| Maximum Width | 36.62 in (930.15 mm) |
| Height | 69.13 in (1755.90 mm) |
| Depth | 17.75 in (450.85 mm) |
| Tightening torque | 375 lbf.in (42.37 N.m) 0.13...0.59 in ² (85.01...380 mm ²) AWG 3/0...750 kcmil) |

Ordering and shipping details

| | |
|-----------------------|----------------------------------|
| Category | 00054 - H&HU SW,NEMA3R,400-1200A |
| Discount Schedule | DE1 |
| GTIN | 00785901259213 |
| Nbr. of units in pkg. | 1 |
| Package weight(Lbs) | 365 lb(US) (165.56 kg) |
| Returnability | No |
| Country of origin | MX |

Offer Sustainability

| | |
|----------------------------|---|
| Sustainable offer status | Green Premium product |
| California proposition 65 | WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov |
| RECh Regulation |  RECh Declaration |
| EU RoHS Directive | Compliant  EU RoHS Declaration |
| Mercury free | Yes |
| RoHS exemption information |  Yes |
| China RoHS Regulation |  China RoHS Declaration |

| | |
|-----------------------------|--|
| Environmental Disclosure |  Product Environmental Profile |
| PVC free | Yes |
| Halogen content performance | Halogen free plastic parts product |
| Contractual warranty | |
| Warranty | 18 months |

Approximate Dimensions

