9422ATCF331

Operating mechanism, flange mounted, variable depth, 30A, 600 V, fuseholder, switch mechanism, 6 inch handle, NEMA 4



Main

Range	9422T
Product	Disconnect Switch
Disconnect Type	Fusible disconnect switch

Complementary

Mounting Type	Flange rod variable depth	
Current Rating	30 A	
Horsepower Rating	7.5 Hp 200 V AC	
	7.5 Hp 230 V AC	
	15 Hp 460 V AC	
	20 Hp 575 V AC	
	5 hp 250 V DC	
Fuse Rating	60 A 250 V	
	30 A 600 V	
Handle Type	6 in handle included NEMA 1/3/3R/4 enclosures sheet steel	
Fuse Type	Н	
	K	
	R	
	J	

Environment

UL Recognized
CSA

Ordering and shipping details

Category	21732 - 9422	
Discount Schedule	CP1	
GTIN	00785901872160	
Nbr. of units in pkg.	1	
Package weight(Lbs)	9 lb(US) (4.08 kg)	
Returnability	Yes	
Country of origin	MX	

Packing Units

PCE	
7.20 in (18.288 cm)	
11.10 in (28.194 cm)	
16.00 in (40.64 cm)	
	7.20 in (18.288 cm) 11.10 in (28.194 cm)

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	☑ REACh Declaration
EU RoHS Directive	Compliant E EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	₫ _{Yes}
China RoHS Regulation	China RoHS Declaration
PVC free	Yes

Contractual warranty

Warranty	18 months	