



Main

Range	TeSys
Device short name	GV7AE
Product or component type	Auxiliary contact block
Device application	Signalling
Range compatibility	TeSys GV5 motor circuit breaker TeSys GV6 motor circuit breaker TeSys GV7 motor circuit breaker
Auxiliary contact composition	1 C/O
Auxiliary contacts type	Standard contacts
Auxiliary contacts operation	Instantaneous
[I _{th}] conventional free air thermal current	6 A IEC 60947-5-1
[U _e] rated operational voltage	<= 690 V AC 50/60 Hz <= 250 V DC
[I _e] rated operational current	6 A AC-12 U _e : <= 690 V IEC 60947-5-1 6 A AC-15 U _e : <= 48 V IEC 60947-5-1 5 A AC-15 U _e : 110...127 V IEC 60947-5-1 4 A AC-15 U _e : 230...240 V IEC 60947-5-1 3 A AC-15 U _e : 380...440 V IEC 60947-5-1 0.1 A AC-15 U _e : 660...690 V IEC 60947-5-1 2.5 A DC-12 U _e : <= 48 V IEC 60947-5-1 0.8 A DC-12 U _e : 110 V IEC 60947-5-1 0.3 A DC-12 U _e : 250 V IEC 60947-5-1 1 A DC-14 U _e : <= 24 V IEC 60947-5-1 0.5 A DC-14 U _e : 48 V IEC 60947-5-1 0.2 A DC-14 U _e : 110 V IEC 60947-5-1 0.05 A DC-14 U _e : 250 V IEC 60947-5-1
Minimum switching current	5 mA
Minimum switching voltage	17 V

Complementary

[U _i] rated insulation voltage	690 V IEC 60947-1
Protection type	GG fuse 10 A maximum GB2CB... circuit breaker 10 A maximum
Mechanical durability	50000 cycles
Mounting location	Inside the circuit breaker
Connections - terminals	Screw clamps terminals 1 0.00 in ² (1.5 mm ²)flexible with cable end Screw clamps terminals 1 0.00 in ² (1.5 mm ²)flexible without cable end Screw clamps terminals 1 0.00 in ² (1.5 mm ²)rigid
Net Weight	0.03 lb(US) (0.015 kg)

Ordering and shipping details






Category	22366 - MAN STR PROTECTORS-GV1/GV3
Discount Schedule	I11
GTIN	00785901566908
Nbr. of units in pkg.	1
Package weight(Lbs)	0.06 lb(US) (0.03 kg)

Returnability	Yes
Country of origin	FR

Packing Units

Unit Type of Package 1	PCE
Package 1 Height	3.15 in (8 cm)
Package 1 width	3.15 in (8 cm)
Package 1 Length	3.15 in (8 cm)
Unit Type of Package 2	BAG
Number of Units in Package 2	10
Package 2 Weight	8.68 oz (246 g)
Package 2 Height	1.57 in (4 cm)
Package 2 width	5.91 in (15 cm)
Package 2 Length	5.91 in (15 cm)
Unit Type of Package 3	S03
Number of Units in Package 3	300
Package 3 Weight	17.84 lb(US) (8.091 kg)
Package 3 Height	11.81 in (30 cm)
Package 3 width	11.81 in (30 cm)
Package 3 Length	15.75 in (40 cm)

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Antimony oxide & Antimony trioxide, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov
REACH Regulation	 REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant  EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	 Yes
China RoHS Regulation	 China RoHS Declaration
Environmental Disclosure	 Product Environmental Profile
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

Contractual warranty

Warranty	18 months
----------	-----------