## Product data sheet Characteristics

## ZCKJD37

limit switch body ZCKJ - fixed - w/o display - 2NC+1NO - slow-break - Pg13





## Main

Range of product	OsiSense XC
Series name	Standard format
Product or component type	Limit switch body
Device short name	ZCKJ
Body type	Fixed
Product compatibility	XCKJ
Associated head	ZCKE619 ZCKE62 ZCKE06 ZCKE05 ZCKE65 ZCKE629 ZCKE63 ZCKE63 ZCKE66 ZCKE61 ZCKE67 ZCKE67 ZCKE21 ZCKE64 ZCKE64
Body material	Metal
Cable entry	1 entry tapped for Pg 13.5 cable gland
Number of poles	3
Contacts type and composition	2 NC + 1 NO
Contact operation	Slow-break, break before make
Number of steps	1 1 position
Contacts material	Silver plated contacts

## Complementary

Local display	Without
Electrical connection	Screw-clamp terminals 1 x 0.342 x 0.75 mm²
Positive opening	With
Minimum actuation speed	6 m/min
[le] rated operational current	1.5 A 240 V, AC-15, B300 EN/IEC 60947-5-1 appendix A 0.1 A 250 V, DC-13, R300 EN/IEC 60947-5-1 appendix A
[Ithe] conventional enclosed thermal current	6 A
[Ui] rated insulation voltage	400 V (pollution degree 3) conforming to IEC 60947-1 for contact block 300 VCSA C22.2 No 14 contact block 300 VUL 508 contact block
Maximum resistance across terminals	0.25 mOhm IEC 60255-7 category 3
[Uimp] rated impulse withstand voltage	6 KV IEC 60664 IEC 60947-1 6 kV
Short-circuit protection	10 A cartridge fuse, type gG
Electrical durability	5000000 Cycles, DC-13 120 V, 4 W 60 cyc/mn 0.5 IEC 60947-5-1 appendix C 5000000 Cycles, DC-13 24 V, 10 W 60 cyc/mn 0.5 IEC 60947-5-1 appendix C 5000000 cycles, DC-13 48 V, 7 W 60 cyc/mn 0.5 IEC 60947-5-1 appendix C
Maximum Width	2.05 in (52 mm)
Height	2.83 in (72 mm)
Depth	1.18 in (30 mm)

Net Weight	0.46 lb(US) (0.21 kg)
Terminals description ISO n°1	(21-22)NC (13-14)NO
Environment	
IP degree of protection	IP66
IK degree of protection	IK05
Ambient air temperature for operation	-13158 °F (-2570 °C) standard environment
Ambient air temperature for storage	-40158 °F (-4070 °C)
Environmental characteristic	Standard environment
Ordering and shipping details	
Category	22411 - LIMIT SWITCHES,IEC,XCKJ
Discount Schedule	Т
GTIN	03389110224894
Nbr. of units in pkg.	1
Package weight(Lbs)	0.8 lb(US) (0.36 kg)
Returnability	No
Country of origin	FR
Packing Units Unit Type of Package 1 Package 1 Height	PCE 1.69 in (4.3 cm)
Package 1 width	3.46 in (8.8 cm)
Package 1 Length	1.77 in (4.5 cm)
<u> </u>	III (I.e only
Offer Sustainability	Croop Bramium product
Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	☑ REACh Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EV RoHS  Declaration
Mercury free	Yes
RoHS exemption information	
Environmental Disclosure	<sup>™</sup> Product Environmental Profile
Combractive Luceure of	
Contractual warranty	

18 months

Warranty