# DTU363AWK

Safety switch, double throw, non fusible, 100A, 600 VAC/VDC, 3 poles, 100 hp, NEMA 12, no knock outs





### Main

Product	Double Throw Safety Switch
Current Rating	100 A
Certifications	UL Listed
Enclosure Rating	NEMA 12 galvannealed steel
Factory Installed Neutral	None
Disconnect Type	Non-fusible disconnect switch
Mounting Type	Surface
Number of Poles	3
Voltage Rating	600 V AC 600 V DC
Wire Size	AWG 12AWG 1/0 aluminium AWG 14AWG 1/0 copper

### Complementary

Short-circuit withstand	200 kA	
Maximum Horse Power Rating	20 Hp 240 V AC 5060 Hz 1 phase NEC 240.6 40 Hp at 240 V AC 5060 Hz for 3 phases motors conforming to NEC 430.52 40 Hp 480 V AC 5060 Hz 1 phase NEC 240.6 75 Hp at 480 V AC 5060 Hz for 3 phases motors conforming to NEC 430.52 40 Hp 600 V AC 5060 Hz 1 phase NEC 240.6 100 Hp at 600 V AC 5060 Hz for 3 phases motors conforming to NEC 430.52 20 Hp at 250 V DC 50 hp at 600 V DC	
Maximum Width	11.96 in (303.78 mm)	
Height	29.94 in (760.48 mm)	
Depth	6.93 in (176.02 mm)	
Tightening torque 35 Lbf.In (3.95 N.m) 0.000.01 in² (2.065.26 mm²) AWG 14AWG 40 Lbf.In (4.52 N.m) 0.01 in² (8.37 mm²) AWG 8) 45 Lbf.In (5.08 N.m) 0.020.08 in² (13.3053.48 mm²) AWG 8) 50 lbf.in (5.65 N.m) 0.040.08 in² (26.6753.48 mm²) AWG 6AWG		

#### Ordering and shipping details

Ordering and shipping details		
Category	00134 - DT SWITCH,NEMA12	
Discount Schedule	DE1	
GTIN	00785901307754	
Nbr. of units in pkg.	1	
Package weight(Lbs)	42 lb(US) (19.05 kg)	
Returnability	Yes	
Country of origin	US	

## **Packing Units**

Unit Type of Package 1	PCE	
Package 1 Height	10.20 in (25.908 cm)	
Package 1 width	12.30 in (31.242 cm)	
Package 1 Length	32.80 in (83.312 cm)	

## Offer Sustainability

Sustainable offer status	Green Premium product	
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov	
REACh Regulation	☑ REACh Declaration	
REACh free of SVHC	Yes	
EU RoHS Directive	Compliant EPEU RoHS Declaration	
Toxic heavy metal free	Yes	
Mercury free	Yes	
RoHS exemption information	₫Yes	
China RoHS Regulation	☑ China RoHS Declaration	
Environmental Disclosure	Product Environmental Profile	

## Contractual warranty

Warranty	18 months