11/8/2017 UL Certification

iq.ul.com

Surge Protective Devices E314042 guide info

Schneider Electric USA, Inc.

Schneider Electric, SURGE PROTECTION BUSINESS, 1751 S 4800 W, Salt Lake City UT 84104

TVS8HWA50X\$*, TVS8HWA80X\$*, TVS8HWA10X\$*, TVS8HWA12X\$*

Permanently Connected

<u>SPD</u> Type	Volts (V)	AC/DC DC PV	<u>Phase</u>	Amps (A)	Ambient Min(°C)	Ambient Max(°C)	<u>Mode</u>	<u>VPR</u> (Vpk)	MCOV (V)	<u>ln</u> (kA)	SCCR (kA)
2	600/347	AC	3Y	n/a	-35	85	4.4	3000	840	20	200
2	000/347	AC	31	II/a	-35	65	L-L			20	200
							L-N	1500	420		
							L-G	2500	840		
							N-G	1500	420		

Evaluated to: UL 1449 4th Ed. Rev: 2017-07-21 and CSA Electrical Certification Notice 516/CSA C22.2 No. 8 13

- \$ May be followed by additional suffixes.
- * Complementary Listed EMI Filters (FOKY), E314042.

SPDs investigated for Type 1 applications are automatically suitable for Type 2 applications and may be marked for SPD Type 1 and/or Type 2 applications. SPDs only marked "SPD Type 2" are not suitable for Type 1 applications.

Where a minimum ambient temperature is not specified, assume 0°C unless the product is marked otherwise or with an Outdoor use Environmental Rating. See Electrical Equipment for Use in Ordinary Locations (AALZ) for details regarding Environmental Ratings.

Report Date: 2009-12-11 Last Revised: 2017-10-24

© 2017 UL LLC

