Product data sheet Characteristics

H362AWC

Safety switch, heavy duty, fusible, 60A, 600 VAC/VDC, 3 poles, 50 hp, NEMA 12K, crouse hinds arktite





Main	
Product	Receptacle Switch
For Use With	Plug APJ6485 Crouse-Hinds Arktite
Current Rating	60 A
Enclosure Rating	NEMA 3R/12 galvannealed steel
Horsepower Rating	15 Hp 480 V AC 5060 Hz 3 phase NEC 240.6 30 Hp 480 V AC 5060 Hz 3 phase NEC 430.52 15 Hp 600 V AC 5060 Hz 3 phase NEC 240.6 50 Hp 600 V AC 5060 Hz 3 phase NEC 430.52 10 hp at 250 V DC conforming to NEC 240.6
Disconnect Type	Fusible disconnect switch
Short Circuit Current Rating	200 KA 10 kA
Mounting Type	Surface
Number of Poles	3
Phase	3 phase
Electrical Connection	Receptacle
Certifications	UL Listed
Voltage Rating	600 V AC 250 V DC
Wire Size	AWG 12AWG 2 aluminium AWG 14AWG 2 copper
Wire Configuration	4-wire

Complementary

Maximum Width	10.5 in (266.70 mm)
Height	16.5 in (419.10 mm)
Depth	7 in (177.80 mm)
Tightening torque	5.08 N.M (AWG 6AWG 4) 4.52 N.M (AWG 8) 35 lbf.in (3.95 N.m) AWG 14AWG 10)

Ordering and shipping details

Category	00118 - H&HU SW,W/C-HINDS RECPT-WC
Discount Schedule	DE1
GTIN	00785901195573
Nbr. of units in pkg.	1
Package weight(Lbs)	27.28 lb(US) (12.37 kg)
Returnability	Yes
Country of origin	US

Packing Units

Unit Type of Package 1	PCE	
Package 1 Height	7.70 in (19.558 cm)	
Package 1 width	14.00 in (35.56 cm)	
Package 1 Length	33.20 in (84.328 cm)	
Unit Type of Package 2	PAL	
Number of Units in Package 2	15	



Package 2 Weight	437.00 lb(US) (198.22 kg)	
Package 2 Height	42.00 in (106.68 cm)	
Package 2 width	40.00 in (101.6 cm)	
Package 2 Length	48.00 in (121.92 cm)	

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Compliant CE EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	₽ Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
PVC free	Yes

Contractual warranty

Warranty

18 months