Product data sheet Characteristics

XVBL4B8 INDICATING BEACON 48VDC 10W +OPTIONS





Main	
Range of product	Harmony XVB Universal
Product or component type	Complete beacon
Beacon or indicator bank unit type	Base unit direct or tube fixing Illuminated unit
Signalling type	Flashing
Mounting diameter	2.76 in (70 mm)
Component name	XVBL
Material	Glass reinforced polyamide: base unit Polycarbonate illuminated unit
Light source	Bulb not included, yellow
Bulb type	Incandescent Incandescent with BA 15d base Protected LED
[Us] rated supply voltage	24 V AC 2448 V DC
Maximum power dissipation in W	7 W

Complementary

Complementary		
Connections - terminals	Screw clamp terminals, <= 1 x 1.5 mm ² with cable end	
[Ui] rated insulation voltage	250 V conforming to IEC 60947-1	
Nominal voltage limit	0.851.1 Un conforming to IEC 60947-5-1	
[Uimp] rated impulse withstand voltage	4 kV IEC 60947-1	
Flashing frequency	1 Hz	
CAD overall width	2.76 in (70 mm)	
CAD overall height	5.47 in (139 mm)	
CAD overall depth	2.76 in (70 mm)	
Terminals description ISO n°1	(GND)GROUND	
	(COM-1)PW	
Net Weight	0.62 lb(US) (0.28 kg)	

Environment

Linnonn		
Pollution degree	2	
Product certifications	CCC UL 508 GOST CSA C22-2 No 14	
Standards	EN/IEC 60947-5-1	
Protective treatment	TC	
Ambient air temperature for storage	-40158 °F (-4070 °C)	
Electrical shock protection class	Class I on support tube conforming to IEC 61140 Class II on base unit conforming to IEC 61140	
IP degree of protection	IP65 on fixing base XVBZ0. conforming to IEC 60529 IP66 on base unit conforming to IEC 60529	
NEMA degree of protection	NEMA 4X conforming to UL 508 (indoor)	

Ordering and shipping details

Category	22611 - XVB-STACKLIGHTS	
Discount Schedule	XV	
GTIN	00785901844235	
Nbr. of units in pkg.	1	
Package weight(Lbs)	0.61 lb(US) (0.28 kg)	
Returnability	No	
Country of origin	CZ	

Packing Units

Unit Type of Package 1	PCE	
Package 1 Height	3.15 in (8 cm)	
Package 1 width	3.15 in (8 cm)	
Package 1 Length	5.71 in (14.5 cm)	
Unit Type of Package 2	S03	
Number of Units in Package 2	18	
Package 2 Weight	11.90 lb(US) (5.4 kg)	
Package 2 Height	11.81 in (30 cm)	
Package 2 width	11.81 in (30 cm)	
Package 2 Length	15.75 in (40 cm)	

Offer Sustainability

Sustainable offer status	Green Premium product	
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov	
REACh Regulation	REACh Declaration	
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) Declaration	
Mercury free	Yes	
RoHS exemption information	₽ Yes	
China RoHS Regulation	China RoHS Declaration	
Environmental Disclosure	Product Environmental Profile	
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.	

Contractual warranty

Warranty

18 months