



Main

Product	Single Throw Safety Switch
Current Rating	200 A
Number of Poles	4
Voltage Rating	600 V AC/DC
Wire Size	AWG 6...250 kcmil copper or aluminium
Disconnect Type	Fusible disconnect
Short Circuit Current Rating	10 KA H or K 200 kA R, J or L
Mounting Type	Surface
Factory Installed Neutral	None
Electrical Connection	Lugs
Duty Rating	Heavy duty
Certifications	UL listed file E2875
Enclosure Rating	NEMA 1 steel

Complementary

Maximum Horse Power Rating	50 Hp 480 V AC 50...60 Hz 2 phases NEC 240.6 125 Hp 480 V AC 50...60 Hz 2 phases NEC 430.52 60 Hp 600 V AC 50...60 Hz 2 phases NEC 240.6 150 Hp 600 V AC 50...60 Hz 2 phases NEC 430.52 40 Hp 250 V DC 50 hp at 600 V DC
Maximum Width	24.88 in (631.95 mm)
Height	29 in (736.60 mm)
Depth	8.75 in (222.25 mm)
Tightening torque	275 lbf.in (31.07 N.m) 0.02...0.20 in ² (13.3...127 mm ²) AWG 6...250 kcmil

Ordering and shipping details

Category	00008 - H&HU SW,2&3P,N1,30-200A
Discount Schedule	DE1
GTIN	00785901482512
Nbr. of units in pkg.	1
Package weight(Lbs)	46 lb(US) (20.87 kg)
Returnability	Yes
Country of origin	US

Packing Units

Unit Type of Package 1	PCE
Package 1 Height	7.13 in (18.11 cm)
Package 1 width	16.50 in (41.91 cm)
Package 1 Length	26.00 in (66.04 cm)

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
PVC free	Yes

Contractual warranty

Warranty	18 months
----------	-----------