Product data sheet Characteristics

ZCKM1

limit switch body ZCKM - 1NC+1NO - snap action - Pg11





Main

Range of product	OsiSense XC
Series name	Standard format
Product or component type	Limit switch body
Device short name	ZCKM
Body type	Fixed
Product compatibility	XCKM
Associated head	ZCKD08 ZCKD06 ZCKD219 ZCKD41 ZCKD02 ZCKD81 ZCKD05 ZCKD16 ZCKD109 ZCKD16 ZCKD15 ZCKD23 ZCKD91 ZCKD029 ZCKD17 ZCKD59 ZCKD17 ZCKD59 ZCKD15 ZCKD21 ZCKD23 ZCKD15 ZCKD021 ZCKD239 ZCKD10
Body material	Metal
Cable entry	3 entries tapped for Pg 11 cable gland
Number of poles	2
Contacts type and composition	1 NC + 1 NO
Contact operation	Snap action
Number of steps	1 1 position
Contacts material	Silver plated contacts

Complementary

Complementary	
Local display	Without
Electrical connection	Screw-clamp terminals, clamping capacity: 1 x 0.342 x 1.5 mm²
Positive opening	With
Minimum actuation speed	0.01 m/min
[le] rated operational current	3 A at 240 V, AC-15, A300 conforming to EN/IEC 60947-5-1 appendix A 0.27 A at 250 V, DC-13, Q300 conforming to EN/IEC 60947-5-1 appendix A
[Ithe] conventional enclosed thermal current	10 A
[Ui] rated insulation voltage	500 V 3)IEC 60947-1 contact block 300 VCSA C22.2 No 14 contact block 300 VUL 508 contact block
Maximum resistance across terminals	0.25 mOhm IEC 60255-7 category 3
[Uimp] rated impulse withstand voltage	IEC 60664 6 kV 6 kV IEC 60947-1
Short-circuit protection	10 A cartridge fuse, type gG
Electrical durability	5000000 Cycles, DC-13 120 V, 7 W 60 cyc/mn 0.5 IEC 60947-5-1 appendix C 5000000 Cycles, DC-13 24 V, 13 W 60 cyc/mn 0.5 IEC 60947-5-1 appendix C 5000000 cycles, DC-13 48 V, 9 W 60 cyc/mn 0.5 IEC 60947-5-1 appendix C
Maximum Width	2.52 in (64 mm)
Height	2.52 in (64 mm)

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not inherenced as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the documentation is not be used to perform the appropriate and complete risk analysis, evaluation of the products with respect to the relevant specific application or use thereof. Neither Schmeider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Depth	1.18 in (30 mm)	
Net Weight	0.46 lb(US) (0.21 kg)	
Terminals description ISO n°1	(21-22)NC (13-14)NO	

Environment

IP degree of protection	IP66	
IK degree of protection	IK05	
Ambient air temperature for operation	-13158 °F (-2570 °C) standard environment	
Ambient air temperature for storage	-40158 °F (-4070 °C)	
Environmental characteristic	Standard environment	

Ordering and shipping details

Category	22416 - LIMIT SWITCHES,IEC,XCKL	
Discount Schedule	Т	
GTIN	00785901646624	
Nbr. of units in pkg.	1	
Package weight(Lbs)	0.52 lb(US) (0.24 kg)	
Returnability	Yes	
Country of origin	ID	

Packing Units

Package 1 Height	0.350 dm
Package 1 width	0.650 dm
Package 1 Length	0.850 dm

Offer Sustainability

Green Premium product
WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Declaration
Pro-active compliance (Product out of EU RoHS legal scope) EV RoHS Declaration
Yes
₫Yes
Product Environmental Profile

Contractual warranty

	Warranty	18 months
--	----------	-----------