2510KO2

Switch, manual, 30A, 3 pole, 10 HP at 575 VAC, three phase, toggle operated, no indicator, open style



Main

Product	Single Unit Manual Switch
Туре	К

Complementary

Complementary	00.4	
Current Rating	30 A	
Horsepower Rating	2 Hp 115 V AC	
	1 Hp 90 V DC	
	2 Hp 115 V DC	
	1.5 Hp 230 V DC	
	7.5 Hp 230 V AC	
	10 Hp 460 V AC	
	10 hp 575 V AC	
Maximum Voltage Rating	600 V AC	
	230 V DC	
Number of Poles	3P	
Control Unit Type	Toggle	
Number of Phases	3 phase	
Pilot Light	No indicator	
Starter Type	Non reversing	
Electrical Connection	Screw clamp terminals	
Wire Gauge	AWG 14AWG 10 copper	
Height	4.13 in (104.90 mm)	
Maximum Width	1.69 in (42.93 mm)	
Depth	2.34 in (59.44 mm)	
Net Weight	0.35 lb(US) (0.16 kg)	

Environment

Certifications	UL recognized E42243 CCN NLRV2 CSA LR25490 class 3211 05	
NEMA Enclosure Rating	Not rated (open device)	
NEMA Enclosure Rating	Not rated (open device)	

Ordering and shipping details

Category	21102 - 2510,2511,2512 K	
Discount Schedule	CP1	
GTIN	00785901554585	
Nbr. of units in pkg.	1	
Package weight(Lbs)	0.35 lb(US) (0.16 kg)	
Returnability	Yes	
Country of origin	MX	

Packing Units

•	
Unit Type of Package 1	PCE
Package 1 Height	2.00 in (5.08 cm)
Package 1 width	4.70 in (11.938 cm)
Package 1 Length	3.00 in (7.62 cm)
Unit Type of Package 2	PAL
Number of Units in Package 2	864
Package 2 Weight	329.00 lb(US) (149.232 kg)
Package 2 Height	40.00 in (101.6 cm)
Package 2 width	40.00 in (101.6 cm)
Package 2 Length	48.00 in (121.92 cm)

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	☑ REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Not compliant
China RoHS Regulation	China RoHS Declaration
PVC free	Yes

Contractual warranty

Warranty	18 months