



## Overview

Lead time	Usually in Stock
-----------	------------------



## Physical

Color	Black
Depth	2.72 in (6.9 cm)
Height	1.73 in (4.4 cm)
Net Weight	0.04 lb(US) (0.02 kg)
Maximum Width	0.75 in (1.9 cm)

## Output

Number of power socket outlets	1
--------------------------------	---

## Conformance

Product certifications	CUL Recognized CE VDE
Standards	UL 497A

## Environmental

Ambient air temperature for operation	5...113 °F (-15...45 °C)
Relative humidity	0...95 %
Operating altitude	0...10000 ft
Ambient air temperature for storage	5...113 °F (-15...45 °C)
Storage altitude	0...10000 ft (0.00...3048.00 m)

## Surge Protection and Filtering

Data Lines Protected (multi-line only)	1-8
NM Surge Response Time (ns)	1 ns common mode
Peak current	0.25 kA common mode 0.2 kA normal mode
Data line protection	RJ45 ISDN / T1 protection



## Ordering and shipping details

GTIN	00731304203377
Package weight(Lbs)	0.11 lb(US) (0.05 kg)

## Packing Units

Package 1 Height	3.90 in (9.9 cm)
Package 1 width	1.30 in (3.3 cm)
Package 1 Length	3.74 in (9.5 cm)
SCC14	30731304203378
Number of Units in Package 2	96
Package 2 Weight	15 lb(US) (6.80 kg)
Package 2 Height	8.125 in (206.38 mm)
Package 2 width	16.25 in (412.75 mm)
Package 2 Length	25.125 in (638.18 mm)

## Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: 1,3-Butadiene, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>
REACH Regulation	 <a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Compliant  <a href="#">EU RoHS Declaration</a>
Lead free	Yes
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

## Contractual warranty

Warranty	Lifetime
----------	----------