

# H366N

Safety switch, heavy duty, fusible, 600A, 3 poles, 500 hp, 600 VAC/DC, neutral factory installed, NEMA1



## Main

Product	Single Throw Safety Switch
Current Rating	600 A
Number of Poles	3
Voltage Rating	600 V AC/DC
Wire Size	AWG 3/0...500 kcmil copper or aluminium
Disconnect Type	Fusible disconnect
Short Circuit Current Rating	10 KA H or K 200 kA R, J or L
Mounting Type	Surface
Factory Installed Neutral	Neutral (factory installed)
Electrical Connection	Lugs
Duty Rating	Heavy duty
Certifications	UL listed file E2875
Enclosure Rating	NEMA 1 steel

## Complementary

Maximum Horse Power Rating	150 Hp 480 V AC 50...60 Hz 3 phase NEC 240.6 400 Hp 480 V AC 50...60 Hz 3 phase NEC 430.52 200 Hp 600 V AC 50...60 Hz 3 phase NEC 240.6 500 Hp 600 V AC 50...60 Hz 3 phase NEC 430.52 50 Hp 250 V DC 50 hp at 600 V DC
Maximum Width	27.63 in (701.80 mm)
Height	50.25 in (1276.35 mm)
Depth	10.13 in (257.30 mm)
Tightening torque	375 lbf.in (42.37 N.m) AWG 3/0...500 kcmil)

## Ordering and shipping details

Category	00053 - H&HU SW,NEMA1,400-1200A
Discount Schedule	DE1
GTIN	00785901451990
Nbr. of units in pkg.	1
Package weight(Lbs)	175 lb(US) (79.38 kg)
Returnability	Yes
Country of origin	MX

## Packing Units

Unit Type of Package 1	PCE
Package 1 Height	14.02 in (35.6 cm)
Package 1 width	27.99 in (71.1 cm)
Package 1 Length	52.01 in (132.1 cm)

## Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>
REACH Regulation	<a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
PVC free	Yes
Halogen content performance	Halogen free plastic parts product

## Contractual warranty

Warranty	18 months
----------	-----------