Product data sheet Characteristics

9422ATCN301

Operating mechanism, flange mounted, variable depth, 30A, 600 V, no fuse, switch mechanism, 6 inch handle, NEMA 4



Main	
Range	9422T
Product	Disconnect Switch
Disconnect Type	Non-fusible disconnect switch

Complementary

Mounting Type	Flange rod variable depth
Current Rating	30 A
Horsepower Rating	7.5 Hp 200 V AC
	7.5 Hp 230 V AC
	15 Hp 460 V AC
	20 Hp 575 V AC
	5 hp 250 V DC
Handle Type	6 in handle included NEMA 1/3/3R/4 enclosures sheet steel

Environment

Certifications	UL Recognized
	CSA

Ordering and shipping details

21732 - 9422
CP1
00785901872146
1
8.23 lb(US) (3.73 kg)
No
MX

Packing Units

Unit Type of Package 1	PCE
Package 1 Height	7.10 in (18.034 cm)
Package 1 width	11.10 in (28.194 cm)
Package 1 Length	16.00 in (40.64 cm)



Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	REACh Declaration
EU RoHS Directive	Compliant CEU RoHS Declaration
Mercury free	Yes
RoHS exemption information	₫ Yes
China RoHS Regulation	China RoHS Declaration
PVC free	Yes

Contractual warranty

Warranty

18 months