

# H364DF

Safety switch, heavy duty, fusible, 200A,  
3 poles, 150 hp, 600 VAC/DC, NEMA 4X,  
fiberglass reinforced polyester



## Main

Product	Single Throw Safety Switch
Current Rating	200 A
Number of Poles	3
Voltage Rating	600 V AC/DC
Wire Size	AWG 6...250 kcmil copper or aluminium
Disconnect Type	Fusible disconnect
Short Circuit Current Rating	10 KA H or K 200 kA R, J or L
Mounting Type	Surface
Factory Installed Neutral	None
Electrical Connection	Lugs
Duty Rating	Heavy duty
Certifications	UL listed file E2875
Enclosure Rating	NEMA 4X fiberglass reinforced polyester

## Complementary

Maximum Horse Power Rating	50 Hp 480 V AC 50...60 Hz 3 phase NEC 240.6 125 Hp 480 V AC 50...60 Hz 3 phase NEC 430.52 60 Hp 600 V AC 50...60 Hz 3 phase NEC 240.6 150 Hp 600 V AC 50...60 Hz 3 phase NEC 430.52 50 hp at 600 V DC
Maximum Width	31.3 in (795.02 mm)
Height	26.3 in (668.02 mm)
Depth	11.8 in (299.72 mm)
Tightening torque	275 lbf.in (31.07 N.m) 0.02...0.20 in <sup>2</sup> (13.3...127 mm <sup>2</sup> ) AWG 6...250 kcmil)

## Ordering and shipping details

Category	00111 - H&HU SW,N4X(DF,DX)NON-MET
Discount Schedule	DE1
GTIN	00785901627876
Nbr. of units in pkg.	1
Package weight(Lbs)	89 lb(US) (40.37 kg)
Returnability	Yes
Country of origin	MX

## Packing Units

Package 1 Height	12.32 in (31.300 cm)
Package 1 width	4.65 in (11.801 cm)
Package 1 Length	10.35 in (26.299 cm)

## Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>
REACH Regulation	<a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
PVC free	Yes

## Contractual warranty

Warranty	18 months
----------	-----------