



### Main

Product or component type	Mechanical lug
Accessory / separate part category	Connection accessory
Quantity per set	Set of 3
Circuit breaker type	P-frame M-frame

### Complementary

Product compatibility	I-Line PowerPact
Line Rated Current	800 A
Material	Aluminium
Mounting mode	Unit mount
Location of connection	Upstream Downstream
AWG gauge	AWG 3/0...600 kcmil aluminium/copper AWG 3/0...750 kcmil aluminium
Kcmil size	750 kcmil
Tightening torque	442.54 lbf.in (50 N.m) 0.15...0.59 in <sup>2</sup> (95...380 mm <sup>2</sup> ) AWG 3/0...750 kcmil)

### Environment

Product certifications	CSA UL
------------------------	-----------

### Ordering and shipping details

Category	01078 - DE2 MISC
Discount Schedule	DE2
GTIN	00785901968467
Nbr. of units in pkg.	1
Package weight(Lbs)	2.51 lb(US) (1.14 kg)
Returnability	Yes
Country of origin	US

### Packing Units

Package 1 Height	3.40 in (8.636 cm)
Package 1 width	5.70 in (14.478 cm)
Package 1 Length	12.80 in (32.512 cm)

## Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: Cancer and Reproductive Harm - <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	<a href="#">End Of Life Information</a>
PVC free	Yes

## Contractual warranty

Warranty	18 months
----------	-----------