## **GV7AU207**

Voltage release, TeSys GV5 GV6 GV7, MN undervoltage trip, 200-240V AC 50/60Hz





Main	
Range	TeSys
Product or component type	Undervoltage trip
Device short name	GV7AS
Device application	Control
Range compatibility	TeSys GV5 TeSys GV6 TeSys GV7

Com	nler	nen	tarv
COILI	pici	11011	tai y

Complementary		
[Uc] control circuit voltage	200240 V AC 50/60 Hz	
Control circuit voltage limits	0.851.1 Un	
[Ui] rated insulation voltage	690 V AC IEC 60947-1 600 V AC UL 508 600 V AC CSA C22.2 No 14	
Threshold tripping voltage	0.350.7 Ue	
Inrush power in VA	10 VA AC	
Hold-in power consumption in VA	5 VA AC	
Operating time	< 50 ms IEC 60947-1	
On-load factor	100 %	
Connections - terminals	Screw clamp terminals 1 0.00 in² (1 mm²)flexible with cable end Screw clamp terminals 1 0.00 in² (1.5 mm²)flexible without cable end Screw clamp terminals 1 0.00 in² (1.5 mm²)solid	
Tightening torque	1.2 N.m screw clamp terminals	
Net Weight	0.23 lb(US) (0.105 kg)	
Quantity per set	Set of 10	

## Ordering and shipping details

Category	22366 - MAN STR PROTECTORS-GV1/GV3	
Discount Schedule	l11	
GTIN	00785901566939	
Nbr. of units in pkg.	1	
Package weight(Lbs)	0.28 lb(US) (0.13 kg)	
Returnability	No	
Country of origin	FR	

## **Packing Units**

Package 1 Height	0.400 dm
Package 1 width	0.830 dm
Package 1 Length	0.630 dm

## Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Antimony oxide & Antimony trioxide, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov
REACh Regulation	☐ REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Compliant EPEU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	₫Yes
China RoHS Regulation	☑ China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

Warranty	18 months
----------	-----------